

GIGA

Quinti®

Advanced operative armchair for the Quinti collection seat with high back available in both white and black.



Dimensions

L TOT 70 L SEAT 50
P TOT 70 P SEAT 45-52 WITH TRANSLATOR
H TOT_ 114/102 H SEAT 45/57

Base

Base "TREND" in polypropylene white or black. [d. 680]
Base "TREND" aluminum. [d. 680]

Castors & feet

Dual tread rubberized with a diameter of 65 mm as standard, they can be free [standard] self-braking. Available also POLO rubberized wheels D.65 [optional].
The polyamide feet are interchangeable with the wheels with the same pin for fixing the base.

Elevation

All Quinti gas columns comply with DIN 4550 standard and exceed the 4th level.

Mechanics

Synchron mechanism in black aluminium.
Seat height adjustment, synchronized adjustment of the seat backrest tilt with anti-shock system lockable in 4 positions. Back oscillation angle 20°, seat oscillation 6,5°.
Oscillation voltage regulation by means of handwheel. Seat sideshift.

Armrests

The armrests made entirely on the backrest block with dynamic adjustment in 4 directions.



Seat.

Made with high strength polypropylene with inserted inside 2 steel bars, always equipped with Sideshift. Padding in cold foam polyurethane rubber density 58 thickness 50 mm for the seat.

Backrest.

Available only in the Gabriel mesh version, in the sample colors. The adjustable lumbar support 3D is applied on the back UP DOWN.



The seat largely exceeds the minimum requirements of DL 626/94, and the DL 81. Complies with EN1335A and approved 1|M

UPHOLSTERY

CREPE' CATEGORY 1

350 gr/mtl
100% Polyester Class 1 ,EN1021/1-2
50.000 +/- 10% Maltindale cycles

BIO-EXPO

CATEGORIA 2

300 gr/mt2
100% Propitex FR bacteriosactic
Classe 1UNI EN ISO 354:2003
100.000 +/- 10% Maltindale cycles

LASER

CATEGORIA 2

560 gr/mtl
100% Polyester FR

Classe 1
80.000+/- 10% Maltindale cycles

ECOPELLE

CATEGORIA 2

630 gr/mt2
83% PVC, 17% Syntetic
ISO 379-DIN75200-CSERF4/83 10%
Maltindale cycles

ERA

CATEGORIA 3

448 gr/mtl
100% Trevira CS
Classe 1UNI EN ISO 354:2003
100.000 +/- 10% Maltindale cycles

LASER PLUS

CATEGORIA 3

630 gr/mtl
100% Polyester FR Trevira
Classe1 , 4.000 +/- Maltindale cycles

ECOPELLE SOUL

CATEGORIA 3

760 gr/mt2
Superficie 100% POLIURHETANE,
Polyester base 85%,17% Cotton
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

MELANGE

CATEGORIA 3

390 g/lin.m
100% Trevira CS
Class 1
80.000 +/- 10% Maltindale cycles

ECOPELLE SISTEMA PRO

CATEGORIA 3

710 gr/mt2
Superficie 93% PVC
Polyester base 28%
CLASS 1
100.000 Cycles

ONE RECYCLE

CATEGORIA 3

525 gr/mt2
100% recycled polyester
Cotton base 100%
CLASS 1IM
100.000 Cycles

ECOPELLE VITAX

CATEGORIA 3

850 gr/mt2
Superficie 98% PVC 2% PU

Cotton base 100%
CLASS 1
100.000 Cycles

VELOURS

CATEGORIA 3

611 gr/mtl
100% Polyester
Oeko test
50.000 +/- 10% Maltindale cycles

COCOON

CATEGORIA 5

980 gr/mtl
43% viscosa 33% cotone 24% li-pl
35.000 +/- 10% Maltindale cycles

LANA

CATEGORIA 5

500 gr/mt2
75% Wool, 25% polyamide
Classe 1
100.000 Maltindale cycles

PELLE

CATEGORIA 5/6

620 g/lin.m
100% Cow leather
Class 1, EN 1021-1/2

PREMIUM /ELEGANCE

CATEGORIA 7

100% Cow leather Primo fiore
Spessore 1,2/1,4 mm
EN1021-1/2

MERIT

CATEGORIA 7

500g/lin.m
76% Polyester Recycled
24% Polyester
EN 1021-1/2
85.000 % Maltindale cycles

STEELCUT TRIO

CATEGORIA 7

770 g/lin.m
90% New wool worsted, 10% Nylon
Class 1, EN 1021-1/2
100.000 % Maltindale cycles

VELLUTO DECONTRACTE'

CATEGORIA 7

590 g/lin.m
19% CO, 61% PC,10% PL, 10%VI
40.000 % Maltindale cycles

VELLUTO

CATEGORIA 8

600 g/lin.m
100.000 % PL Flame retardant

PELLE SOFT

CATEGORIA 8

100% Cow leather SPESSORE1,8-2 mm
Primo fiore CONCIA ALL'ANILINA
EN1021-1/2-35.000 % Maltindale cycles

RETI

RETE GABRIEL

510 gr. gr/mtl
100% Polyester BS EN 1021-1:2014
70.000 rubs

RETE GOAL

350 gr/mq
100% Polyester BS EN 1021-1:2014 100% Poliester / Polyester CL. 1
100.000 Rubs

USAGE AND CARE

For an optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.

FABRICS

Cleaning: check the dedicated selection written on the color Swatch card. Usage: it is recommended to pay attention to the fabrics as they can be easily cut or ripped.

LEATHERS

Cleaning: clean with a white wet cloth with water. We recommend using high quality products for the cleaning of the leather to follow carefully the instructions of the manufacturer. In doubt, try out the product on a hidden part and wait at least 24 hours for the occurrence of any problems. Usage: remember that the leather is a delicate material therefore, it is recommended to pay particular attention while using.

WOODS

Cleaning: clean with a soft and wet cloth with warm water. We always recommend drying immediately after the cleaning process. All liquids or other residue must be removed in order to avoid the absorption. Usage: wooden surfaces, being a natural material, could be affected by an alteration of the color shade during time and use. We also remind that wooden surfaces cannot bear with high temperatures if placed directly on the wooden top.

METALS

Cleaning: both steel or aluminum surfaces, and painted ones, must be cleaned with a soft and wet cloth with hot water. For the most persistent stains, a small amount of liquid soap diluted in water may be used. We always recommend drying immediately with a soft cloth or a leather one after the cleaning process. Never using cleaning products for steel, chlorine, bleach or other strong detergents. It is not recommended to use abrasive creams, score pads and abrasive sponges that can scratch the metal surfaces. Usage: pay attention to the stains of food such as coffee, coke, fruit juices that can leave indelible marks on the surface.

WARRANTY

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or material supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.