ARWA Archirivolto design



ARWA armchair designed for classical and modern spaces, characterized by researched and elegant materials for a timeless result.

2 3











6



- 1. Armchair with armrests 4 metal legs
- 2. Armchair with armrests 4 wooden legs
- 3. Armchair with armrests 4 spokes metal swivel base
- 4 . Armchair no armrests 4 metal legs
- 5 . Armchair no armrests 4 wooden legs 6 . Stool 4 metal legs

L58/45 P 60/46 H78/47 L58/45 P 60/46 H78/47 L70/45 P 70/45 H78/47 L52/43 P 62/46 H83/47 L52/43 P 62/46 H83/47 L52/43 P 62/46 H100/75 or 92/65



Quinti[®]

FRAME

4 metal legs dim. 15*30 mm, available finishes:

- Black painted
- Quinti colours painted (min 10 pz)

4 wooden legs

- Natural wooden finish
- Moka wooden finish

4 metal legs dim. 15*30 mm with footrest, available finishes:

- Black painted
- Quinti colours painted (min 10 pz)

Two heights available: 75 cm and 65 cm.



INNER FRAME AND PADDING

Inner structure in wood and injected foam. Elastic straps in the seat to grant the highest comfort.

1IM certified

ACCESSORIES



METAL FEET



Quinti®

UPHOLSTERY

BIO-EXPO CATEGORY 2

300 gr/mt2 100% Propitex FR bacteriostatic Class 1UNI EN ISO 354 :2003 100.000 +/- 10% cycles Martindale

LASER CATEGORY 2

560 gr/mtl 100% Polyester FR Class 1 80.000+/- 10% cycles Martindale

ECOPELLE CATEGORY 2

630 gr/mt2 83% PVC, 17% Synthetic ISO 379-DIN75200-CSERF4/83 10% cycles Martindale

ERA CATEGORY 3

448 gr/mtl 100% Trevira CS Class 1UNI EN ISO 354 :2003 100.000 +/- 10% cycles Martindale

LASER PLUS CATEGORY 3

630 gr/mtl 100% Polyester FR Trevira Class1, 4.000 +/- cycles Martindale

ECOPELLE SOUL CATEGORY 3

760 gr/mt2 Superficies 100% POLYURETHANE, Base Polyester 85%,17% Cotton EN1021-1/BS5852 PART 1 >100.000 EN ISO 5470-2

MELANGE CATEGORY 3

390 g/lin.m 100% Trevira CS Class 1 80.000 +/- 10% cycles Martindale

JET CATEGORY 3 365+/- 5% g/lin.m

100% Polyester FR Class 1 80.000+/- 10% cycles Martindale ONE RECYCLED CATEGORY 3

525 gr/mt2 100% recycled polyester Base cotton 100% CLASS 1IM 100.000 CYCLES

ECOPELLE SISTEMA PRO CATEGORY 3

710 gr/mt2 Surface 93% PVC Base Polyester 28% CLASS1 100.000 CYCLES

VELOURS CATEGORY 3

100% Polyester. BASE: 100% Polyester EN 14465:2006 CLASS 1

ECOPELLE VITAX CATEGORY 3

850 gr/mt2 Surface 98% PVC 2% PU Base cotton 100% CLASS 1 100.000 CYCLES

LANA CATEGORY 5

500 gr/mt2 75% Lana, 25% polyamide Class 1 100.000 cycles Martindale

COCON CATEGORY 5

43% Viscous 33% Cotton 15% Linen 9% Polyester EN ISO 12945-2 EN ISO 12947-2 Class 1

PELLE CATEGORY 5/6 620 g/lin.m

100% Cow leather Class 1, EN 1021-1/2

STEELCUT TRIO CATEGORY 7

770 g/lin.m 90% New wool worsted, 10% Nylon Class 1, EN 1021-1/2 100.000 % cycles Martindale MERIT CATEGORY 7

500g/lin.m 76% Polyester Recycled 24% Polyester EN 1021-1/2 85.000 % cycles Martindale

PREMIUM CATEGORY 7

100% First quality cow leather Thickness 1,2/1,4 mm EN1021-1/2

VELLUTO DECONTRACTE'
CATEGORY 7

590 g/lin.m 19% CO, 61% PC,10% PL, 10%VI 40.000 % cycles Martindale

VELLUTO CATEGORY 7/8 600 g/lin.m

100.000 % PL Flame retardant

PELLE ELEGANCE CATEGORY 7

100% Cow leather Thickness,8-2 mm Aniline treatment – First quality EN1021-1/2

PELLE SETA CATEGORY 8

100% Cow leather Thickness,8-2 mm Crome treatment – First quality EN1021-1/2





USAGE AND CARE

In order to have an optimal maintenance of the products and to preserve the characteristics of the materials by which they are made, it is recommended the following course of action.

FABRICS

Cleaning: check the dedicated selection written on the color Swatch card.

Usage: it is recommended to pay careful attention to the fabrics as they can be cut or ripped easily.

WOODS

Cleaning: clean using a soft cloth, soaked in tepid water. Dry always after the cleaning. Remove immediately any liquid substances or other residue in order to prevent the absorption.

Usage: wooden surfaces, being a natural material, might be subjected to color alterations with sun exposure and use over time. It is reminded that wooden surfaces cannot endure direct heat sources.

METALS

Cleaning: both steel and aluminum surfaces, and the painted ones, have to be cleaned using a soft cloth soaked in tepid water. For the most persistent stains it is possible to dilute mild soap with water moderately. Dry always after the cleaning, using a soft cloth o deer-hide. Do not use cleaning products for steel, chlorine, bleach or other strong products. It is not recommended to use abrasive, scourers, which can scratch the metal surfaces.

Usage: pay attention to the food stains as coffee, coke, fruit juices that can make indelible marks on the surfaces.

WARRANTY

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.