

DEEP STOOL Archirivolto design

Quinti®

DEEP STOOL recalls the shape of the Quinti DEEP collection. This comfortable stool is characterized by a short backrest and armrests. It can be upholstered in all Quinti fabrics.

1



2



3



- 1. 4 metal legs frame
- 2. 4 wooden legs frame
- 3. Black painted rounded

- L. 52/45 – P. 50/42 – H. 98/77
- L. 52/45 – P. 50/42 – H. 98/77
- L. 52/45 – P. 54/45 – H. 80-107/60-87 (diameter 42 cm)

STRUCTURE

- **4 metal legs** (16mm diam) with footrest, available in the following finishes:
 - Black Painted
 - Gold Painted
 - Quinti colors (min 10 pcs)
- **4 legs frame with footrest in oak wood:**
 - Natural
 - Moka
- **Rounded base** with footrest, swiveling and adjustable in height – black painted.
- **Base with floor fixing** without footrest, swiveling and adjustable in height.

INNER STRUCTURE AND PADDING

The inner structure is made of metal and has a diameter of 10 mm.
Elastic belts included in the seat to grant extra comfort. The pad is made of cold polyurethane foam.

1IM Certified

DEEP STOOL Archirivolto design

Quinti®

UPHOLSTERY

BIO-EXPO CATEGORY 2

300 gr/mt2
100% Propitex FR bacteriostatic
Class 1 UNI EN ISO 354 :2003
100.000 +/- 10% cycles Martindale

LASER CATEGORY 2

560 gr/mtl
100% Polyester FR
Class 1
80.000 +/- 10% cycles Martindale

ECOPELLE CATEGORY 2

630 gr/mt2
83% PVC, 17% Synthetic
ISO 379-DIN75200-CSERF4/83 10%
cycles Martindale

ERA CATEGORY 3

448 gr/mtl
100% Trevira CS
Class 1 UNI EN ISO 354 :2003
100.000 +/- 10% cycles Martindale

LASER PLUS CATEGORY 3

630 gr/mtl
100% Polyester FR Trevira
Class 1, 4.000 +/- cycles Martindale

ECOPELLE SOUL CATEGORY 3

760 gr/mt2
Superficies 100% POLYURETHANE,
Base Polyester 85%, 17% Cotton
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

MELANGE CATEGORY 3

390 g/lin.m
100% Trevira CS
Class 1
80.000 +/- 10% cycles Martindale

JET CATEGORY 3

365 +/- 5% g/lin.m
100% Polyester FR
Class 1
80.000 +/- 10% cycles Martindale

ONE RECYCLED CATEGORY 3

525 gr/mt2
100% recycled polyester
Base cotton 100%
CLASS 1IM
100.000 CYCLES

ECOPELLE SISTEMA PRO CATEGORY 3

710 gr/mt2
Surface 93% PVC
Base Polyester 28%
CLASS1
100.000 CYCLES

VELOURS CATEGORY 3

100% Polyester.
BASE: 100% Polyester
EN 14465:2006
CLASS 1

ECOPELLE VITAX CATEGORY 3

850 gr/mt2
Surface 98% PVC 2% PU
Base cotton 100%
CLASS 1
100.000 CYCLES

LANA CATEGORY 5

500 gr/mt2
75% Lana, 25% polyamide
Class 1
100.000 cycles Martindale

COCON CATEGORY 5

43% Viscous 33% Cotton
15% Linen 9% Polyester
EN ISO 12945-2 EN ISO 12947-2
Class 1

PELLE CATEGORY 5/6

620 g/lin.m
100% Cow leather
Class 1, EN 1021-1/2

STEELCUT TRIO CATEGORY 7

770 g/lin.m
90% New wool worsted, 10% Nylon
Class 1, EN 1021-1/2
100.000 % cycles Martindale

MERIT CATEGORY 7

500g/lin.m
76% Polyester Recycled
24% Polyester
EN 1021-1/2
85.000 % cycles Martindale

PREMIUM CATEGORY 7

100% First quality cow leather
Thickness 1,2/1,4 mm
EN1021-1/2

VELLUTO DECONTRACTE' CATEGORY 7

590 g/lin.m
19% CO, 61% PC, 10% PL, 10%VI
40.000 % cycles Martindale

VELLUTO CATEGORY 7/8

600 g/lin.m
100.000 % PL Flame retardant

PELLE ELEGANCE CATEGORY 7

100% Cow leather Thickness, 8-2 mm
Aniline treatment – First quality
EN1021-1/2

PELLE SETA CATEGORY 8

100% Cow leather Thickness, 8-2 mm
Crome treatment – First quality
EN1021-1/2

USAGE AND CARE

In order to have an optimal maintenance of the products and to preserve the characteristics of the materials by which they are made, it is recommended the following course of action.

FABRICS

Cleaning: check the dedicated selection written on the color Swatch card.

Usage: it is recommended to pay careful attention to the fabrics as they can be cut or ripped easily.

WOODS

Cleaning: clean using a soft cloth, soaked in tepid water. Dry always after the cleaning. Remove immediately any liquid substances or other residue in order to prevent the absorption.

Usage: wooden surfaces, being a natural material, might be subjected to color alterations with sun exposure and use over time. It is reminded that wooden surfaces cannot endure direct heat sources.

METALS

Cleaning: both steel and aluminum surfaces, and the painted ones, have to be cleaned using a soft cloth soaked in tepid water. For the most persistent stains it is possible to dilute mild soap with water moderately. Dry always after the cleaning, using a soft cloth of deer-hide. Do not use cleaning products for steel, chlorine, bleach or other strong products. It is not recommended to use abrasive, scourers, which can scratch the metal surfaces.

Usage: pay attention to the food stains as coffee, coke, fruit juices that can make indelible marks on the surfaces.

WARRANTY

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.
