

CLICK

Quinti®



High-back operational chair from the Quinti collection.

The session largely exceeds the minimum requirements of Legislative Decree 626/94, and Legislative Decree 81.

This chair is in compliance with EN1335A and 1IM approved.

Base

1. Black polypropylene base "LOOP" [d. 600]
2. Polished aluminum base "LOOP" [d. 680]

Castors and feet

Double-tread with a diameter of 50 mm, standard [series] or wheeled, both can be free [standard] or self-braking.

Elevation

All the Quinti gas column comply with the DIN 4550 standard and pass the 4th level.

Mechanism

Synchron mechanism in black aluminum with seat height adjustment and synchronized seat backrest inclination adjustment with anti-shock system lockable in 2 positions. Adjustment of the swing tension by means of a knob placed under the seat.

Armrests

Available armrests:

1. Pair of fixed armrests in black polypropylene
2. Pair of height-adjustable nylon armrests
3. Pair of 3d armrests with polyurethane pad



Seat and backrest

Seat. Upholstered without seams, with internal wooden support padded with polyurethane foam 60 mm thick, non-deformable T40 density.

Backrest. Available as standard in the goal net version, in the colors of the samples, it is equipped with adjustable lumbar support. The structure is in black or white polypropylene.

CLICK

Quinti®

UPHOLSTERY

LASER

CATEGORY 2

560 gr/mtl
100% Polyester FR
Class 1
80.000+/- 10% cycles Martindale

MELANGE

CATEGORY 3

390 g/lin.m
100% Trevira CS
Class 1
80.000 +/- 10% cycles Martindale

PREMIUM /ELEGANCE

CATEGORY 7

100% Cow leather Thickness,8-2 mm
Aniline treatment – First quality
EN1021-1/2

ECOPELLE

CATEGORY 2

630 gr/mt2
83% PVC, 17% Synthetic
ISO 379-DIN75200-CSERF4/83 10%
cycles Martindale

VELOURS

CATEGORY 3

100% Polyester.
BASE: 100% Polyester
EN 14465:2006
CLASS 1

STEELCUT TRIO

CATEGORY 7

770 g/lin.m
90% New wool worsted, 10% Nylon
Class 1, EN 1021-1/2
100.000 % cycles Martindale

JET

CATEGORY 3

365+/- 5% g/lin.m
100% Polyester FR
Class 1
80.000+/- 10% cycles Martindale

ECOPELLE SISTEMA PRO

CATEGORY 3

710 gr/mt2
Surface 93% PVC
Base Polyester 28%
CLASS1
100.000 cycles Martindale

BOUCLET

CATEGORY 7

860 g/lin.m
40% PC, 25%PL,20%VI, 15% CO
Class 1, EN 1021-1/2
50.000 % cycles Martindale

ONE RECYCLED

CATEGORY 3

525 gr/mt2
100% recycled polyester
Base cotton 100%
CLASS 1IM
100.000 cycles Martindale

COCOON

CATEGORY 5

43% Viscous 33% Cotton
15% Linen 9% Polyester
EN ISO 12945-2 EN ISO 12947-2
Class 1

MERIT

CATEGORY 7

600 g/lin.m
100.000 % PL Flame retardant

ERA

CATEGORY 3

448 gr/mtl
100% Trevira CS
Class 1UNI EN ISO 354 :2003
100.000 +/- 10% cycles Martindale

WOOL

CATEGORY 5

500 gr/mt2
75% Lana, 25% polyamide
Class 1
100.000 cycles Martindale

VELLUTO

CATEGORY 8

600 g/lin.m
100.000 % PL Flame retardant

CHILI

CATEGORY 3

470 gr/mtl
100% post-consumer recycled polyester
Classe1 - 60.000 +/- cycles Martindale

GLAMOUR

CATEGORY 5

700 g/lin.m
100% Recycled Polyester
EN 1021-1/2
80.000 % cycles Martindale

PELLE SETA

CATEGORY 8

100% Cow leather Thickness,8-2 mm
Crome treatment – First quality
EN1021-1/2

ECOPELLE SOUL

CATEGORY 3

760 gr/mt2
Superficies 100% POLYURETHANE,
Base Polyester 85%,17% Cotton
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

PELLE

CATEGORIA 5/6

620 g/lin.m
100% Cow leather
Class 1, EN 1021-1/2

ZERO

CATEGORY 8

750g/lin.m
65% CO, 20% PAN, 15% PES
70.000 % cycles Martindale

LYRA

CATEGORIA 3

550 g/lin.m
100% polyester
Class 1
60.000 +/- 10% cycles Martindale

VELLUTO DECONTRACTE'

CATEGORY 7

590 g/lin.m
19% CO, 61% PC,10% PL, 10%VI
40.000 % cycles Martindale

USAGE AND CARE

In order to have an optimal maintenance of the products and to preserve the characteristics of the materials by which they are made, it is recommended the following course of action.

FABRICS

Cleaning: check the dedicated selection written on the color Swatch card.

Usage: it is recommended to pay careful attention to the fabrics as they can be cut or ripped easily.

WOODS

Cleaning: clean using a soft cloth, soaked in tepid water. Dry always after the cleaning. Remove immediately any liquid substances or other residue in order to prevent the absorption.

Usage: wooden surfaces, being a natural material, might be subjected to color alterations with sun exposure and use over time. It is reminded that wooden surfaces cannot endure direct heat sources.

METALS

Cleaning: both steel and aluminum surfaces, and the painted ones, have to be cleaned using a soft cloth soaked in tepid water. For the most persistent stains it is possible to dilute mild soap with water moderately. Dry always after the cleaning, using a soft cloth or deer-hide. Do not use cleaning products for steel, chlorine, bleach or other strong products. It is not recommended to use abrasive, scourers, which can scratch the metal surfaces.

Usage: pay attention to the food stains as coffee, coke, fruit juices that can make indelible marks on the surfaces.

WARRANTY

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.
