

## AMELIE BASSA



Ergonomic and directional armchair with low backrest characterized by generous dimensions.

### **BASE**

---

1. Die-cast aluminum Boch diam. 670 mm
2. Shop base 4 races swivel on castors or feet. D. 650
3. Star base 4 races on feet. D. 650
5. Rod chromed base for 1403 version

### **CASTORS**

---

Dual tread with 65 mm diameter. Standard [standard] or rubberized, both can be free [series] or self-braking. The polyamide feet are interchangeable with the wheels with the same pin for fixing to the base.

### **ELEVATION**

---

All Quinti gas columns comply with DIN 4550 standard and exceed the 4 year level.  
In the Shop base the base is swivel but not adjustable in height.

### **MECHANICS**

---

1. **M5** the standard configuration of the chair supposes a tilt single lever mechanism with gas command, height and block in operative position. It has a wheel for the variation of the tilt rigidity. The main body is entirely made out of die-cast aluminum.
2. **M4 / M3**[optional] the point of rotation of this mechanism is advanced. The blocking lever allows the blocking process in 3 positions with a backstop system of the seat. It has a wheel for the variation of the tilting rigidity. The main body is entirely made out of shiny or black die-cast aluminum.
3. **M10** [optional] harmonic mechanism, which guarantees a permanent tilt of the seat and gas elevation.
4. **M8/M8F** swivel plate with or without elevation depending on the base

### **ARMRESTS**

---

The armchair can host the two different models:

1. couplet of armrests in chrome-plated
2. full armrests completely covered.

### **SEAT & BACKREST**

---

For every version, the seat and backrest are made up of an aluminum structure with elastic belts, entirely cold foamed.

### **PADDING**


---

Standard upholsters made with expanded polyurethane cold foamed available in the GLUE, SOLFT and SLIM versions.



## AMELIE BASSA

### DIMENSIONS



## UPHOLSTERIES

---

### LASER

#### CATEGORY 2

560 gr/mtl  
100% Polyester FR  
Class 1  
80.000+/- 10% Maltindale cycles

### ECOPELLE

#### CATEGORY 2

630 g/lin.m  
83% PVC 17% Synthetic  
Class 1  
30.000 +/- 10% Maltindale cycles

### JET

#### CATEGORY 3

365+/- 5% g/lin.m  
100% Polyester FR  
Class 1  
80.000+/- 10% Maltindale cycles

### ONE RECICLED

#### CATEGORY 3

525 gr/mt2  
100% recycled poliester  
CLASS 1IM  
100.000 CYCLES

### ERA

#### CATEGORY 3

448 gr/mtl  
100% Trevira CS  
Class 1UNI EN ISO 354:2003  
100.000 +/- 10% Maltindale cycles

### CHILI

#### CATEGORY 3

470 gr/mtl  
100% post-consumer recycled polyester  
Class1 - 60.000 +/- Maltindale cycles

### ECOPELLE SOUL

#### CATEGORY 3

760 gr/mt2  
SURFACE 100% POLYURETHANE,  
Base Polyester 85%,17% Cotton  
EN1021-1/BS5852 PART 1  
>100.000 EN ISO 5470-2

### LYRA

#### CATEGORY 3

550 g/lin.m  
100% Polyester  
Class 1

### MELANGE

#### CATEGORY 3

390 g/lin.m  
100% Trevira CS  
Class 1  
80.000 +/- 10% cycles Martindale

### VELOURS

#### CATEGORY 3

611 gr/mtl  
100% Polyester  
Oeko test  
50.000 +/- 10% Maltindale cycles

### COCOON

#### CATEGORY 5

980 gr/mtl  
43% viscosa 33% cotone 24% li-pl  
35.000 +/- 10% Maltindale cycles

### LANA

#### CATEGORY 5

500 gr/mt2  
75% wool, 25% polyamide  
Class 1  
100.000 Maltindale cycles

### GLAMOUR

#### CATEGORY 5

700 g/lin.m  
100% Polyester Recycled  
EN 1021-1/2  
80.000 % Maltindale cycles

### LEATHER

#### CATEGORY 5/6

620 g/lin.m  
100% cow leather  
Class 1, EN 1021-1/2

### VELLUTO DECONTRACTE'

#### CATEGORY 7

590 g/lin.m  
19% CO, 61% PC,10% PL, 10%VI  
40.000 % Maltindale cycles

### PREMIUM /ELEGANCE

#### CATEGORY 7

100% Grained cow leather  
Thickness 1,2/1,4 mm  
EN1021-1/2

### STEELCUT TRIO

#### CATEGORY 7

770 g/lin.m  
90% New wool worsted, 10% Nylon  
Class 1, EN 1021-1/2  
100.000 % Maltindale cycles

### BOUCLET

#### CATEGORY 7

860 g/lin.m  
40% PC, 25%PL,20%VI, 15% CO  
Class 1, EN 1021-1/2  
50.000 % Maltindale cycles

### MERIT

#### CATEGORY 8

500g/lin.m  
76% Polyester Recycled  
24% Polyester  
EN 1021-1/2  
85.000 % Maltindale cycles

### VELLUTO

#### CATEGORY 8

600 g/lin.m  
100.000 % PL Flame retardant

### LEATHER SETA

#### CATEGORY 8

100% Leather bovina THICKNESS1,8-2 mm  
Grained cow leather aniline tannage  
EN1021-1/2

### ZERO

#### CATEGORY 8

750g/lin.m  
65% CO, 20% PAN, 15% PES  
70.000 % Maltindale cycles

## USAGE AND CARE

---

For a proper maintenance of the products and to maintain unchanged the characteristics of the materials, we recommend to follow some very simple care instructions.

### FABRICS

Cleaning: check the dedicated selection written on the color Swatch card. Usage: it is recommended to pay attention to the fabrics as they can be easily cut or ripped.

### LEATHERS

Cleaning: clean with a white wet cloth with water. We recommend to use high quality products for the cleaning of the leather and to follow carefully the instructions of the manufacturer. In doubt, try out the product on a hidden part and wait at least 24 hours for the occurrence of any problems. Usage: remember that the leather is a delicate material therefore, it is recommended to pay particular attention while using.

### WOODS

Cleaning: clean with a soft and wet cloth with warm water. We always recommend to dry immediately after the cleaning process. All liquids or other residue must be removed in order to avoid the absorption. Usage: wooden surfaces, being a natural material, could be affected by an alteration of the color shade during time and use. We also remind that wooden surfaces cannot bear with high temperatures if placed directly on the wooden top.

### METALS

Cleaning: both steel or aluminum surfaces, and painted ones, must be cleaned with a soft and wet cloth with hot water. For the most persistent stains, a small amount of liquid soap diluted in water may be used. We always recommend to dry immediately with a soft cloth or a leather one after the cleaning process. Never using cleaning products for steel, chlorine, bleach or other strong detergents. It is not

## AMELIE BASSA

recommended to use abrasive creams, score pads and abrasive sponges that can scratch the metal surfaces. Usage: pay attention to the stains of food such as coffee, coke, fruit juices that can leave indelible marks on the surface.

### **WARRANTY**

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.