

NEW SPEED

Quinti®

Ergonomic task chair, large and comfortable.



DIMENSIONS

LARGHEZZA
WIDTH

68
49

PROFONDITÀ
DEPTH

68
46

ALTEZZA
HEIGHT

100/112
44/56

SEAT & BACKREST

Back: black or white polypropylene structure, equipped with adjustable lumbar support covered in soft membrane type Goal New.

Seat: Made with FSC beech plywood interior and black polypropylene underseat. Polyurethane foam inlay, 50 mm thick. Double-stitched and coated.

ARMRESTS

- Fixed armrests
- Adjustable armrests in height (black or white nylon)
- 3D adjustable armrests with soft polyurethane pad available in both black and white with black pad

NEW SPEED

MECHANISM

SPEED is equipped with the Synchron mechanism in black aluminum.



1. Adjustable seat height
2. Free-swinging
3. Swing locked 5 positions
4. Voltage regulation
5. Seat shifter [Optional]

Gas column complies with DIN 4550 and exceeds 4.

BASE

It is available with 3 types of base:

- "TREND" 5-spoke on polished aluminium wheels [d. 680 mm]
- "TREND" 5-spoke on black polypropylene wheels [d. 680 mm]

Standard black nylon double tread wheels with 65 mm diameter
Optional with the same fixing pin diameter 11mm:

- Black (R06) or grey rubber wheels with chrome housing (R07),
- Black rubber wheels and self-braking (R06A),
- Wheels "polo" with central hole
- Black nylon feet (R08)

SEAT CERTIFICATIONS

- 1IM fire reaction approval
- EN1335-B

CRITERIA GPP SEAT

All the materials used for the production of this product are low emissive according to UNI EN 16000-9 below 500 µg/m³.

- Plastics
- Fabrics
- Padding

Also for this the product offered complies with the requirements required in the Ministerial Decree CAM



DISASSEMBLY

SPEED has been designed to allow for life-cycle assembly, so that its parts and components can be reused, recycled or recovered for energy purposes

USE & MAINTENANCE

For optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.

FABRICS

Cleaning: see the maintenance and washing advice given in the color chart.

Usage: It is recommended to pay attention to the use as it can be torn or cut.

LEATHERS

Cleaning: clean with a damp white cloth soaked in water only. Use quality products according to the instructions of the manufacturer.

If in doubt, we recommend that you test the product on a part hidden from view to verify the result, waiting at least 24 hours for possible problems.

Use: remember that the leather is a delicate material therefore; it is recommended to take care during use.

WOODS

Cleaning: Clean with a damp, soft cloth soaked in warm water. Always dry after cleaning.

Remove any liquid or other residue immediately to prevent absorption.

Use: wood surfaces, being a natural material, may, over time, undergo color changes with use and exposure to light.

Remember that the wood cannot withstand direct heat sources on the surface.

METALS

Cleaning: Both metal surfaces made of steel or aluminum, as well as painted surfaces, must be cleaned with a damp and soft cloth soaked in hot water.

For stubborn stains, you can dilute the liquid neutral soap in water with moderation. Always dry after cleaning with a soft cloth or with deer leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other aggressive detergents. Do not use abrasive pastes, scouring pads and sponges that can scratch metal surfaces.

Use: be careful of stains from food such as coffee, cola, fruit juices that can leave indelible stains on surfaces

WARRANTY

QUINTI guarantees that the products will keep their characteristics for 6 years from delivery, save normal wear and provided they are used according to the indications given. QUINTI will replace any product found not to comply with this warranty at no cost, without bearing any other liability. The warranty is excluded for components, external accessories or materials supplied by the buyer and applied to products for the purpose of a customization of the same. For optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.

NEW SPEED

UPHOLSTERIES

LASER

CATEGORY 2

560 gr/mtl
100% Polyester FR
Class 1
80.000 +/- 10% Maltindale cycles

ECOPELLE

CATEGORY 2

630 g/lin.m
83% PVC 17% Synthetic
Class 1
30.000 +/- 10% Maltindale cycles

JET

CATEGORY 3

365 +/- 5% g/lin.m
100% Polyester FR
Class 1
80.000 +/- 10% Maltindale cycles

ONE RECICLED

CATEGORY 3

525 gr/mt2
100% recycled poliester
CLASS 1IM
100.000 CYCLES

ERA

CATEGORY 3

448 gr/mtl
100% Trevira CS
Class 1UNI EN ISO 354:2003
100.000 +/- 10% Maltindale cycles

CHILI

CATEGORY 3

470 gr/mtl
100% post-consumer recycled polyester
Class 1 - 60.000 +/- Maltindale cycles

ECOPELLE SOUL

CATEGORY 3

760 gr/mt2
Surface 100% POLYURETHANE,
Base Polyester 85%, 17% Cotton
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

LYRA

CATEGORY 3

550 g/lin.m
100% Polyester
Class 1
60.000 +/- 10% Maltindale cycles

MELANGE

CATEGORY 3

390 g/lin.m
100% Trevira CS
Class 1
80.000 +/- 10% Maltindale cycles

VELOURS

CATEGORY 3

611 gr/mtl
100% Polyester
Oeko test
50.000 +/- 10% Maltindale cycles

ECOPELLE SISTEMA PRO

CATEGORY 3

710 g/lin.m
93% PVC 7% polyester
Class 1
100.000 +/- 10% Maltindale cycles

COCOON

CATEGORY 5

980 gr/mtl
43% viscose 33% cotton 24% li-pl
35.000 +/- 10% Maltindale cycles

LANA

CATEGORY 5

500 gr/mt2
75% wool, 25% polyamide
Class 1
100.000 Maltindale cycles

GLAMOUR

CATEGORY 5

700 g/lin.m
100% Polyester Recycled
EN 1021-1/2
80.000 % Maltindale cycles

PELLE

CATEGORY 5/6

620 g/lin.m
100% Cowhide
Class 1, EN 1021-1/2

VELLUTO DECONTRACTE'

CATEGORY 7

590 g/lin.m
19% CO, 61% PC, 10% PL, 10%VI
40.000 % Maltindale cycles

PREMIUM /ELEGANCE

CATEGORY 7

100% Cowhide Primo fiore
Thickness 1,2/1,4 mm
EN1021-1/2

STEELCUT TRIO

CATEGORY 7

770 g/lin.m
90% New wool worsted, 10% Nylon
Class 1, EN 1021-1/2
100.000 % Maltindale cycles

BOUCLET

CATEGORY 7

860 g/lin.m
40% PC, 25%PL, 20%VI, 15% CO
Class 1, EN 1021-1/2
50.000 % Maltindale cycles

MERIT

CATEGORY 8

500g/lin.m
76% Polyester Recycled
24% Polyester
EN 1021-1/2
85.000 % Maltindale cycles

VELLUTO

CATEGORY 8

600 g/lin.m
100.000 % PL Flame retardant

PELLE SETA

CATEGORY 8

100% Cowhide THICKNESS 1,8-2 mm
First flower TANNING WITH ANILINE
EN1021-1/2

ZERO

CATEGORY 8

750g/lin.m
65% CO, 20% PAN, 15% PES
70.000 % Maltindale cycles