<u>Level X</u> Quinti



Executive armchair with generous shapes and foam upholstered backrest.

Seat & Backrest

The back with integrated armrests padded in cold-foamed polyurethane rubber duly coated and sewn double stitching.

The fully upholstered seat, sewn with double side stitching made of 8 cm thick cold-foamed polyurethane.

Mechanic

Weight-activated synchronized mechanism integrated with the under-seat. Seat height adjustment and synchronised adjustment of the backrest/seat inclination equipped with anti Shock lockable in 4 positions. (All controls are integrated in the underseat with small levers.)

The gas column complies with DIN 4550 and exceeds level 4

Base

Two types of bases:

5-spokes "BOCK" on polished aluminium wheels [d. 680 mm] 5-spokes "BOCK" on black painted aluminium wheels [d. 680 mm]

Standard black nylon double tread wheels with 65 mm diameter.

Measures	Height's seat	Total height	Width	Depth
cm	47/57	94/104	70/55	70/50
cm	47/57	108/118	70/55	70/50

Product's certificates









Level X



Disassemblability

All products have been designed in such a way that they can be disassembled at the end of their useful life, so that their parts and components can be reused, recycled or recovered for energy purposes.

Guarantee and safety

QUINTI guarantees that the products will keep their characteristics for 6 years from delivery, save normal wear and provided they are used according to the indications given. QUINTI will replace any product found not to comply with this warranty at no cost, without bearing any other responsibility. The application of the component warranty is excluded; external accessories or materials provided by the buyer and applied to products for the purpose of a customization of the same. For optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, Some simple attentions are required.

All the sessions offered are SAFE according to the provisions of the EU Regulation 2023/988, on general product safety (GPSR), reinforced by UNI EN certifications.

The company is not liable for misuse (Stand up or use products such as ladders and oscillations that could affect the operation and safety of the user. To lift or move the product, grasp firmly on the supporting structure. The product must not be subjected to decentralized loads, is designed to be used in normal standing conditions on 4 legs or on the base).

Uso e Manutenzione

For an optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.

THE FABRICS

Cleaning: consult the recommendations for maintenance and washing given in the fabric sheet of the color chart. Use: It is recommended to pay attention to the use as it is can be torn or cut.

THE LEATHERS

Cleaning: clean with a damp white cloth soaked in water only. Use high-quality leather care products according to the manufacturer's instructions. In case of doubt, test the product on a part hidden from view to verify the result, waiting at least 24 hours for possible problems. Use: remember that the leather is a delicate material therefore it is recommended to take care during use.

THE METALS

Cleaning: both metal surfaces made of steel or aluminium, as well as painted surfaces, must be cleaned with a damp and soft cloth soaked in hot water. For the most stubborn stains, you can dilute liquid neutral soap in water with moderation. Always dry after cleaning with a soft cloth or deer leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and sponges that can scratch metal surfaces. Use: be careful of food stains such as coffee, cola, fruit juices that can leave indelible stains on surfaces.

Level X



Upholsteries

LASER GRADE 2 560 gr/mtl

100% Polyester FR

Classe 1

80.000+/- 10% cicli Maltindale

ECOPELLE GRADE 2

630 g/lin.m

83% PVC 17% Synthetic

Classe 1

30.000 +/- 10% cicli Maltindale

JET GRADE 3 365+/- 5% g/lin.m 100% Polyester FR

Classe 1

80.000+/- 10% cicli Maltindale

ONE RECICLED GRADE 3 525 gr/mt2

100% recycled poliester CLASSE 1IM

LYRA GRADE 3 550 g/lin.m

100.000 CICLI

100% Polyester Classe 1

60.000 +/- 10% cicli Maltindale

CHILI GRADE 3 470 gr/mtl

100% post-consumer recycled polyester

- 60.000 +/- cicli Maltindale

DREAM GRADE 3

375gr/mtl 100% Polyester solution dyed melange bouclè effect OEKO TEST

Classe1 - 100.000 +/- cicli Maltindale

MELANGE GRADE 3 390 g/lin.m 100% Trevira CS

Classe 1

80.000 +/- 10% cicli Maltindale

VELOURS GRADE 3

611 gr/mtl 100% Polyester Oeko test

50.000 +/- 10% cicli Maltindale

ECOPELLE SOUL GRADE 3

760 gr/mt2

Surface 100% POLIURETANO, Base Polyester 85%,17% Cotton EN1021-1/BS5852 PART 1 >100.000 EN ISO 5470-2

COCOON GRADE 5

980 gr/mtl

43% viscose 33% cotton 24% li-pl 35.000 +/- 10% cicli Maltindale

LANA GRADE 5 500 gr/mt2

75% Wool, 25% polyamide

Classe 1

100.000 cicli Maltindale

GLAMOUR GRADE 5

700 g/lin.m 100% Polyester Recycled

EN 1021-1/2

80.000 % cicli Maltindale

TECHNICOLOUR kvadral

GRADE 5

430 g/lin. M

100% new English wool, worsted 80.000 % cicli Maltindale

Ecolabel

Classe 1

MAIN LINE camira

GRADE 5 437 g/lin.m

75% Virgin wool, 25% Linen

Classe 1, Ecolabel

50.000 +/- cicli Maltindale

PELLE GRADE 5/6

620 g/lin.m 100% Cowhide Classe 1, EN 1021-1/2 PELLE PREMIUM UP/ELEGANCE

GRADE 7

100% first flower cowhide Width 1,2/1,4 mm EN1021-1/2

MONOCHROME SETT camira

GRADE 7 437 g/lin.m

75% Virgin wool, 25% Linen

Classe 1, Ecolabel

50.000 +/- cicli Maltindale

BOUCLET PUBLICA

GRADE 7

860 g/lin.m 40% PC, 25%PL,20%VI, 15% CO

Classe 1, EN 1021-1/2

50.000 % cicli Maltindale

VELLUTO DECONTRACTE' RUBELLI

GRADE 7

590 g/lin.m

19% CO, 61% PC,10% PL, 10% VI

40.000 % cicli Maltindale

HORO RUBELU GRADE 7

495 g/lin.m

44%PL 29%CO 24%JU 3%PC

30.000 % cicli Maltindale

PELLE SETA

GRADE 8

100% Cowhide width1,8-2 mm

first-grain leather

EN1021-1/2

ZERO GRADE 8

750g/lin.m

65% CO, 20% PAN, 15% PES

70.000 % cicli Maltindale