CLICK



Ergonomic task chair



DIMENSIONS

LARGHEZZA WIDTH 68 46

PROFONDITÁ DEPTH 68 46 ALTEZZA HEIGHT 99/111 43/55

SEAT & BACKREST

Backrest: load-bearing structure in black polypropylene, equipped with an adjustable lumbar support covered in a Goal New type soft membrane.

Sedile: Realizzato con interno in multistrato di faggio FSC e sotto sedile in polipropilene nero. Imbottitura in Gomma poliuretanica Seat: Made with FSC beech plywood interior and black polypropylene under seat. Padding in non-deformable polyurethane rubber, 50 mm thick. Double stitched coated and sewn.

ARMS

- o Fixed arms
- o Height-adjustable armrests in black or white nylon

MECHANISM

CLICK with a black aluminium Syncron mechanism.



- 1. Seat height adjustment
- 2. Free oscillation
- 3. Oscillation blocked 5 positions
- 4. Voltage adjustment handwheel
- 5. Seat Slide [Optional]

The gas column complies with DIN 4550 and exceeds 4° level

BASE

PUNTA" 5 spokes on castors black polyproypelene [d. 600 mm]

Standard castors in black nylon double tread with diameter of 60 mm R01

CLICK



CHAIR CERTIFICATES

- · 1IM fire reaction approval
- · EN 1335-B

Disassemblability

All products have been designed in such a way that they can be disassembled at the end of their useful life, so that their parts and components can be reused, recycled or recovered for energy purposes.

Guarantee and safety

QUINTI guarantees that the products will keep their characteristics for 6 years from delivery, save normal wear and provided they are used according to the indications given. QUINTI will replace any product found not to comply with this warranty at no cost, without bearing any other responsibility. The application of the component warranty is excluded; external accessories or materials provided by the buyer and applied to products for the purpose of a customization of the same. For optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, Some simple attentions are required.

All the sessions offered are SAFE according to the provisions of the EU Regulation 2023/988, on general product safety (GPSR), reinforced by UNI EN certifications.

The company is not liable for misuse (Stand up or use products such as ladders and oscillations that could affect the operation and safety of the user. To lift or move the product, grasp firmly on the supporting structure. The product must not be subjected to decentralized loads, is designed to be used in normal standing conditions on 4 legs or on the base).

Use & Maintenance

For an optimal maintenance of the products and to maintain unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.

THE TEXTILES

Cleaning: consult the recommendations for maintenance and washing given in the fabric sheet of the color chart. Use: It is recommended to pay attention to the use as it is can be torn or cut.

THE LEATHERS

Cleaning: clean with a damp white cloth soaked in water only. Use high-quality leather care products according to the manufacturer's instructions. In case of doubt, test the product on a part hidden from view to verify the result, waiting at least 24 hours for possible problems. Use: remember that the leather is a delicate material therefore it is recommended to take care during use.

THE METALS

Cleaning: both metal surfaces made of steel or aluminium, as well as painted surfaces, must be cleaned with a damp and soft cloth soaked in hot water. For the most stubborn stains, you can dilute liquid neutral soap in water with moderation. Always dry after cleaning with a soft cloth or deer leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and sponges that can scratch metal surfaces. Use: be careful of food stains such as coffee, cola, fruit juices that can leave indelible stains on surfaces.

UPHOLSTERY

Available in an only upholstery Crepè

Weight 350 gr/mtl - Composition. 100% Polyester, Approval / Flammability. Class 1, EN 1021-1 EN 1021-2, Abrasion Test Maltindale UNI EN ISO 12945/1. 50.000+/- 10% cicli

