PAT monocoque in polypropylene or versatile wood capable of integrating into any environment.



SHELL

Available in three variants:

• 6 mm thick embossed polypropylene monocoque, with soft lines, without edges. Available colors:



Oak wood monocoque with beveled profile available in the finishes:



 Wooden monocoque padded with 3 cm thick polyurethane rubber and covered. Packaged with double stitching and horizontal stitching "STRIPE". The fabric is glued to the rubber to prevent creasing over time during use.

2 3 4 1 5 6 7 8 9 10 11 12 13 14

DIMENSIONS

- Armchair with 4-legged frame
 Armchair with rod frame
- 3. Armchair with rod frame NEW
- 4. Armchair with 4 wooden legs
- 5. Armchair with 4-legged frame and armrests
- 6. Armchair with 4-leg frame and armrests and tablet
- 7. Armchair with inverted cantilever frame s/br
- L52/44P 54/40 H78/44
- L52/44 P 54/40 H78/44
- L57/44 P 54/40 H78/44
- L56/44 P 58/40 H78/44
- 8. Armchair with cantilever frame and armrests
- 9. Armchair with Leggera 4-spoke base
- 10. Armchair with Punta/Trend 5-spoke base
- 11. Armchair with 4-spoke wooden base
- 12.Stool 4 legs
- 13. 5-spoke basic stool and footrest ring
- 14. Basic stool with 5 spokes and integrated footrest
- L56/44 P 54/40 H78/44
- L70/44 P 70/40 H81/90-47/56
- L70/44 P 70/40 H81/90-47/56
- L70/44 P 70/40 H78/45 L46/44 P 52/40 H109/72
- L70/44 P 70/40 H90/109-55/72
- L70/44 P 70/40 H90/109-55/72

- Frame 4 metal legs (diameter 16 mm) available with integrated armrests and tablet, in the finishes:
- Chromed
- Standard black painted
- Standard painted white
- NEW rod bar/ rod frame (11 mm diameter) with nylon feet in the finishes:
- Chromed
- Standard black painted
- Standard painted white
- Frame 4 legs in painted oak wood in the finishes:
- Natural
- Moka
- Walnut
- Black open pore
- Light base 4 spokes in polished aluminium (diameter 70 cm) swivel (with elevation) available with wheels or feet.
- Trend 5-spoke base on wheels (diameter 68 cm) swivel (with elevation) available in:
- Polished aluminium
- Polypropylene black
- Polypropylene white
- 4-spoke swivel base (without elevation) in painted oak wood
- Natural
- Moka
- Walnut
- Black open pore
- Metal cantilever frame made with tubular diam 20 mm, with or without armrests in the finishes:
- Standard painted white
- Standard black painted
- Frame stool 4 legs made of tubular diam 16 mm in finishes:
- Standard painted white
- Standard black painted
- Frame stool with ring footrest and 5-spoke base (diameter 68 cm) on feet available in:
- -aluminium glossy
- -polypropylene white
- -Black polypropylene
- 2, 3 or 4-seater bench structure with white painted metal trestle leg (available in pair of polished aluminium legs). The shells are hooked with omega fixing and plate under seat on beam 80x40 mm painted white or grey aluminium







3

1. DIM 2P L120/44 P 61/4 H78/42

2. DIM 3P L175/44 P 61/4 H78/42

3. DIM 4P L238/44 P 61/4 H78/42

ACCESSORIES

Chromed wire armrests Wooden arms Metal hook for online connection Trolley

SEAT CERTIFICATE

- CL1 fire reaction approval
- Complies with the CAM Ministerial Decree
- EN16139:2013 LIV 1 (EN1022 EN1728)
- ESC
- ReMade Plastic

Disassembly

All products have been designed in such a way as to allow them to be disassembled at the end of their useful life, so that their parts and components can be reused, recycled, or recovered for anergy purposes.

Warranty and Safety

QUINTI guarantees that the products will retain their characteristics for 6 years from delivery, except for normal wear and tear and provided that they are used in accordance with the instructions provided. QUINTI will replace any product fount not to comply with this warranty at no cost, without incurring any other liability whatsoever. The warranty does not apply to components, external accessories, or materials supplied by the buyer and applied to the products for the purpose of customizing them. For optimal maintenance of the products and to preserve the characteristics of the materials with which they are made, a few simple precautions are necessary.

All chairs offered are SAFE in accordance with EU Regulations 2023/988on general product safety (GPSR), reinforced by UNI EN certifications.

The company shall not be held liable if the product is used improperly (standing on it or using it as a ladder, or swinging it in a way that could compromise its functioning and the user's safety). To lift or move the product, grasp it firmly by the supporting structure. The product must not be subjected to off-center loads; it is designed to be used under normal conditions, resting on its four legs or base.

Usage and Care

For optimal maintenance of the products and to preserve the characteristics of the materials they are made of, a few simple precautions are necessary.

FARRICS

Cleaning: please refer to the care and washing instructions provided in the fabric section of the color chart. Use: it is recommended to take care when using them as they can be torn or cut.

LEATHERS

Cleaning: clean with a damp white cloth soaked in water only. Use high-quality leather cleaning products, carefully following the manufacturer's instructions. If in doubt, test the product on a hidden area to check the result, waiting at least 24 hours to see if any problems arise

. Use: please remember that leather is a delicate material, so care should be taken when using it.

METALS

Cleaning: both steel and aluminum metal surfaces, should be cleaned with a soft damp cloth soaked in warm water. For stubborn stains, you can dilute a small amount of mild liquid soap in water. Always dry after cleaning with a soft cloth or chamois leather. Do not use creams or pastes to clean steel, do not use chlorine, bleach, or other aggressive detergents. Do not use abrasive pastes, scouring pads, or abrasive sponges, as they may scratch metal surfaces.

Use: be careful with food stains such as coffee, cola, and fruit juice, which can leave permanent stains on surfaces.

WOODS

Cleaning: clean with a soft, damp cloth soaked in warm water. Always dry after cleaning. Immediately remove any liquids or other residues to prevent absorption.

Use: wood surfaced, being a natural material, may undergo color changes over time with use and exposure to light. Please note that wood cannot withstand direct heat sources on its surface.

UPHOLSTERIES

LASER CATEGORY 2

560 gr/mtl 100% Polyester FR Class 1

80.000+/- 10% Maltindale cycles

ECOPELLE CATEGORY 2

630 g/lin.m 83% PVC 17% Synthetic Class 1

30.000 +/- 10% Maltindale cycles

JET

CATEGORY 3 365+/- 5% g/lin.m 100% Polyester FR

Class 1

80.000+/- 10% Maltindale cycles

ONE RECYCLED CATEGORY 3

525 gr/mt2 100% recycled poliester CLASS 1IM 100.000 Cycles

LYRA
CATEGORY 3

550 g/lin.m 100% Polyester Class 1

60.000 +/- 10% Maltindale cycles

CHILI CATEGORY 3

470 gr/mtl

100% post-consumer recycled polyester - 60.000 +/- Maltindale cycles

DREAM CATEGORY 3

375gr/mtl 100% Mass-dyed polyester Bouclè effect melange OEKO TEST

Class 1 - 100.000 +/- Maltindale cycles

MELANGE CATEGORY 3

390 g/lin.m 100% Trevira CS Class 1

80.000 +/- 10% Maltindale cycles

VELOURS
CATEGORY 3

611 gr/mtl 100% Polyester Oeko test

50.000 +/- 10% Maltindale cycles

ECOPELLE SOUL CATEGORY 3

760 gr/mt2 Surface 100% Polyurethane, Base 85% polyester,17% Cotton EN1021-1/BS5852 PART 1 >100.000 EN ISO 5470-2

COCOON CATEGORY 5 980 gr/mtl

43% viscose 33% cotton 24% li-pl

35.000 +/- 10% Maltindale cycles

LANA
CATEGORY 5

500 gr/mt2 75% Wool, 25% polyamide Class 1

100.000 Maltindale cycles

GLAMOUR CATEGORY 5

Class 1

700 g/lin.m 100% Recycled polyester EN 1021-1/2

80.000 % Maltindale cycles

TECHNICOLOUR kvadral CATEGORY 5

430 g/lin. M 100% new English wool, worsted 80.000 % Maltindale cycles Ecolabel

MAIN LINE cames CATEGORY 5 437 g/lin.m 75% Virgin Wool, 25% Linen Class 1, Ecolabel

50.000 +/- Maltindale cycles

PELLE CATEGORY 5/6

620 g/lin.m 100% Cowhide eather Class 1, EN 1021-1/2 PELLE PREMIUM UP/ELEGANCE CATEGORY 7

100% Full-grain cowhide leather

Thickness 1,2/1,4 mm EN1021-1/2

MONOCHROME SETT camira CATEGORY 7

437 g/lin.m

75% Virgin Wool, 25% Linen

Class 1, Ecolabel

50.000 +/- Maltindale cycles

BOUCLET RUBELLI CATEGORY 7 860 g/lin.m

40% PC, 25%PL,20%VI, 15% CO

Class 1, EN 1021-1/2

50.000 % Maltindale cycles

VELLUTO DECONTRACTE' RUBELLI

CATEGORY 7

590 g/lin.m 19% CO, 61% PC,10% PL, 10%VI

40.000 % Maltindale cycles

HORO RUMELU
CATEGORY 7

495 g/lin.m

44%PL 29%CO 24%JU 3%PC

30.000 % Maltindale cycles

PELLE SETA CATEGORY 8

100% Cowhide leather, THICKNESS 1,8-2 rr

First Aniline Tanning EN1021-1/2

ZERO CATEGORY 8

750g/lin.m

65% CO, 20% PAN, 15% PES 70.000 % Maltindale cycles