



SEAT & BACKREST

Monocoque entirely made of cold foamed. In the lumbar part, two elastic straps ensure better comfort. Available with glued coating or “soft” with an interposition of “wadding” with soft stitching.

BASE

Different bases are available:

- Structure 4 legs in chrome or painted metal tubular (black-white)
- o Chrome wire ring structure
- o 4-spoke Base Shop on feet with swivel mechanism and elevation
- o Base 4 spokes in natural dyed wood, mocha, walnut or open pore black.
- o 5-spoke base loop on wheels with swivel mechanism and elevation



Measures	Seat height	Total height	Width	Depth
4 LEGS	46	79	51/47	50/43
ROD	45	78	53/47	50/43
4 SPOKES	45	78	68/47	68/43
4 WOODEN SPOKES	46	76	70/47	70/43
5 SPOKES	45/55	82/92	68/47	68/43

SEAT CERTIFICATE

o 1IM fire reaction approval

CRITERI GPP SEDUTA

All materials used to make the product are low emissives in accordance with the UNI EN 16000-9 Standard, less than 500 µg/m3.

- Plastics
- Painted metals

For this reason too, the product offered complies with the requirements required in the CAM Ministerial Decree

DISASSEMBLY

HYWAY has been designed in such a way that it can be assembled at the end of its useful life, so that its parts and components can be reused, recycled or recovered for energy purposes

USE & MAINTENANCE

For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

THE FABRICS

Cleaning: See the maintenance and washing tips on the fabric tab of the color chart. Use: Careful use is advised as they can be torn or cut.

THE LEATHERS

Cleaning: Clean with a damp white cloth soaked in water only. Use quality leather cleaning products by carefully following the instructions of the cleaning product manufacturer. If in doubt, it is recommended to test the product on a part hidden from view to verify the result, waiting at least 24 hours for any problems to arise.

Use: Remember that the skin is a delicate material therefore it is recommended to take care during use.

PLASTICS

Cleaning: Plastic surfaces should generally be cleaned with a damp, soft cloth soaked in water. It is not recommended to use dry cloths, which, when rubbed, could electrostatically charge the plastic surface, attracting dust. For more stubborn stains, you can dilute liquid neutral soap in water in moderation. Absolutely avoid using acetone, trielin, ammonia, or detergents that contain even a small amount of these detergents because they can dull the shine of surfaces.

Avoid all abrasive substances, such as detergent powders, abrasive pastes, scouring pads, or rough sponges, absolutely.

Use: Avoid dragging objects that can line the material onto surfaces. Also remember, that plastic materials cannot withstand direct heat sources on the surface

METALS

Cleaning: Both steel or aluminum metal surfaces, as well as painted surfaces, should be cleaned with a damp, soft cloth soaked in hot water. For more stubborn stains, you can dilute liquid neutral soap in water in moderation.

Always dry after cleaning with a soft cloth or chamois leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other harsh detergents. It is not recommended to use abrasive pastes, scouring pads, and abrasive sponges that can scratch metal surfaces. Use: Watch out for stains on foods such as coffee, cola, fruit juices that can leave permanent stains on surfaces

WARRANTY

QUINTI guarantees that the products will maintain their characteristics for 6 years from delivery, without prejudice to normal wear and tear and provided that they are used according to the instructions provided. QUINTI will replace any product found to be non-compliant with the said warranty without incurring any other liability whatsoever. The application of the warranty on components, external accessories or materials supplied by the buyer and applied to the products for the purpose of personalizing them is excluded. For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

All sessions offered are SAFE according to the provisions of EU Regulation 2023/988, on General Product Safety (GPSR), strengthened by UNI EN certifications.

The company does not hold itself liable if it is misused (Standing up or using products such as ladders and swings that could compromise the operation and safety of the user. To lift or move the product grip firmly on the supporting structure. The product must not be subjected to off-center loads, it is designed to be used under normal conditions of support on 4 legs or on the base).

Upholsteries

LASER

CATEGORY 2

560 gr/mtl
100% Poliestere FR
Classe 1
80.000 +/- 10% cicli Maltindale

VELOURS

CATEGORY 3

611 gr/mtl
100% Poliestere
Oeko test
50.000 +/- 10% cicli Maltindale

PELLE PREMIUM UP/ELEGANCE

CATEGORY 7

100% Pelle bovina Primo fiore
Spessore 1,2/1,4 mm
EN1021-1/2

ECOPELLE

CATEGORY 2

630 g/lin.m
83% PVC 17% Sintetico
Classe 1
30.000 +/- 10% cicli Maltindale

ECOPELLE SOUL

CATEGORY 3

760 gr/mt2
Superficie 100% POLIURETANO,
Base Poliestere 85%, 17% Cotone
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

MONOCHROME SETT

CATEGORY 7

437 g/lin.m
75% Lana Vergine, 25% Lino
Classe 1, Ecolabel
50.000 +/- cicli Maltindale

JET

CATEGORY 3

365 +/- 5% g/lin.m
100% Poliestere FR
Classe 1
80.000 +/- 10% cicli Maltindale

COCOON

CATEGORY 5

980 gr/mtl
43% viscosa 33% cotone 24% li-pl
35.000 +/- 10% cicli Maltindale

BOUCLET

CATEGORY 7

860 g/lin.m
40% PC, 25% PL, 20% VI, 15% CO
Classe 1, EN 1021-1/2
50.000 % cicli Maltindale

ONE RECICLE

CATEGORY 3

525 gr/mt2
100% recycled poliester
CLASSE 1IM
100.000 CICLI

LANA

CATEGORY 5

500 gr/mt2
75% Lana, 25% poliammide
Classe 1
100.000 cicli Maltindale

VELLUTO DE CONTRACTE'

CATEGORY 7

590 g/lin.m
19% CO, 61% PC, 10% PL, 10% VI
40.000 % cicli Maltindale

LYRA

CATEGORY 3

550 g/lin.m
100% Poliestere
Classe 1
60.000 +/- 10% cicli Maltindale

GLAMOUR

CATEGORY 5

700 g/lin.m
100% Poliestere Recycled
EN 1021-1/2
80.000 % cicli Maltindale

HORO

CATEGORY 7

495 g/lin.m
44% PL 29% CO 24% JU 3% PC
30.000 % cicli Maltindale

CHILI

CATEGORY 3

470 gr/mtl
100% post-consumer recycled polyester
- 60.000 +/- cicli Maltindale

TECHNICOLOUR

CATEGORY 5

430 g/lin. M
100% new English wool, worsted
80.000 % cicli Maltindale
Ecolabel
Classe 1

PELLE SETA

CATEGORY 8

100% Pelle bovina SPESSORE 1,8-2 mm
Primo fiore CONCIA ALL'ANILINA
EN1021-1/2

DREAM

CATEGORY 3

375 gr/mtl
100% Poliestere tinto in massa
melange effetto bouclè
OEKO TEST
Classe 1 - 100.000 +/- cicli Maltindale

MAIN LINE

CATEGORY 5

437 g/lin.m
75% Lana Vergine, 25% Lino
Classe 1, Ecolabel
50.000 +/- cicli Maltindale

ZERO

CATEGORY 8

750 g/lin.m
65% CO, 20% PAN, 15% PES
70.000 % cicli Maltindale

MELANGE

CATEGORY 3

390 g/lin.m
100% Trevira CS
Classe 1
80.000 +/- 10% cicli Maltindale

PELLE

CATEGORY 5/6

620 g/lin.m
100% Pelle bovina
Classe 1, EN 1021-1/2