



Base

1. In 670 mm die-cast aluminum, type "Loop"
 2. Cantilever structure, slide base
 3. In 670 mm black polypropylene, type "Loop"
- Also available in the Noire version with black painted armrests and base

Castors

Double tread with diameter 60 mm., standard [standard] or rubberized, both can be free [standard] or self breaking. The polyamide feet are interchangeable with the wheels with the same fixing pin to the base.

Elevation

All Quinti gas columns comply with DIN 4550 and exceed 4° level.

Mechanics

M5 The chair is equipped with a single-lever oscillating mechanism with gas height control and locking in the operating position. It is completed with flyer for varying the oscillation hardness. The supporting body is entirely constructed of die-cast aluminium.

M4 [optional] The point of rotation of this mechanism has advanced. The locking lever allows locking in 3 positions with anti-return seat system. It is complete with handwheel for varying the oscillation hardness. The supporting body is entirely constructed of die-cast aluminium.

M3 [optional] Advanced plus oscillating mechanism that allows for height adjustment of the seat, free oscillation of the backrest with locking in four positions. Oscillating voltage adjustment, polished aluminium.

M8 Rotating plate with elevation

Armrests

1. Pair of chrome steel armrests
2. Pair of chrome plated and coated armrests (Maybe Special)
3. Pair of black painted metal armrests (Noire)



Seat & backrest

The seat and backrest consist of a 12 MM multi-layered beech monocoque, adequately padded and covered with double padding with a density of 40 sp.3 cm.

SEAT CERTIFICATE

- IIM fire reaction approval



Measures	Type	Seat height	Total height	Width	Depth
Cm	Alta	42/52	107/117	68/53	68/48
cm	Bassa	42/52	84/94	68/53	68/48
cm	Cantilever c/br	44	88	59/53	67/48
cm	Cantilever s/br	44	88	59/53	67/48

Upholsteries

LASER

CATEGORY 2

560 gr/mtl
100% Poliestere FR
Classe 1
80.000 +/- 10% cicli Maltindale

ECOPELLE

CATEGORY 2

630 g/lin.m
83% PVC 17% Sintetico
Classe 1
30.000 +/- 10% cicli Maltindale

JET

CATEGORY 3

365 +/- 5% g/lin.m
100% Poliestere FR
Classe 1
80.000 +/- 10% cicli Maltindale

ONE RECICLE

CATEGORY 3

525 gr/mt2
100% recycled poliester
CLASSE 1IM
100.000 CICLI

LYRA

CATEGORY 3

550 g/lin.m
100% Poliestere
Classe 1
60.000 +/- 10% cicli Maltindale

CHILI

CATEGORY 3

470 gr/mtl
100% post-consumer recycled polyester
- 60.000 +/- cicli Maltindale

DREAM

CATEGORY 3

375gr/mtl
100% Poliestere tinto in massa
melange effetto bouclè
OEKO TEST
Classe1 - 100.000 +/- cicli Maltindale

MELANGE

CATEGORY 3

390 g/lin.m
100% Trevira CS
Classe 1
80.000 +/- 10% cicli Maltindale

VELOURS

CATEGORY 3

611 gr/mtl
100% Poliestere
Oeko test
50.000 +/- 10% cicli Maltindale

ECOPELLE SOUL

CATEGORY 3

760 gr/mt2
Superficie 100% POLIURETANO,
Base Poliestere 85%,17% Cotone
EN1021-1/BS5852 PART 1
>100.000 EN ISO 5470-2

COCOON

CATEGORY 5

980 gr/mtl
43% viscosa 33% cotone 24% li-pl
35.000 +/- 10% cicli Maltindale

LANA

CATEGORY 5

500 gr/mt2
75% Lana, 25% poliammide
Classe 1
100.000 cicli Maltindale

GLAMOUR

CATEGORY 5

700 g/lin.m
100% Poliestere Recycled
EN 1021-1/2
80.000 % cicli Maltindale

TECHNICOLOUR kvadrat

CATEGORY 5

430 g/lin. M
100% new English wool, worsted
80.000 % cicli Maltindale
Ecolabel
Classe 1

MAIN LINE camira

CATEGORY 5

437 g/lin.m
75% Lana Vergine, 25% Lino
Classe 1, Ecolabel
50.000 +/- cicli Maltindale

PELLE

CATEGORY 5/6

620 g/lin.m
100% Pelle bovina
Classe 1, EN 1021-1/2

PELLE PREMIUM UP/ELEGANCE

CATEGORY 7

100% Pelle bovina Primo fiore
Spessore 1,2/1,4 mm
EN1021-1/2

MONOCHROME SETT camira

CATEGORY 7

437 g/lin.m
75% Lana Vergine, 25% Lino
Classe 1, Ecolabel
50.000 +/- cicli Maltindale

BOUCLET RUBELLI

CATEGORY 7

860 g/lin.m
40% PC, 25%PL,20% VI, 15% CO
Classe 1, EN 1021-1/2
50.000 % cicli Maltindale

VELLUTO DECONTRACTE' RUBELLI

CATEGORY 7

590 g/lin.m
19% CO, 61% PC,10% PL, 10% VI
40.000 % cicli Maltindale

HORO RUBELLI

CATEGORY 7

495 g/lin.m
44%PL 29%CO 24%JU 3%PC
30.000 % cicli Maltindale

PELLE SETA

CATEGORY 8

100% Pelle bovina SPESSORE1,8-2 mm
Primo fiore CONCIA ALL'ANILINA
EN1021-1/2

ZERO

CATEGORY 8

750g/lin.m
65% CO, 20% PAN, 15% PES
70.000 % cicli Maltindale

CRITERIA GPP SEAT

All materials used to make the product are low emissives in accordance with the UNI EN 16000-9 Standard, less than 500 µg/m³.

- Plastics
- Painted metals

For this reason too, the product offered complies with the requirements required in the CAM Ministerial Decree

DISASSEMBLY

Maybe has been designed in such a way that it can be assembled at the end of its useful life, so that its parts and components can be reused, recycled or recovered for energy purposes

USE & MAINTENANCE

For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

THE FABRICS

Cleaning: See the maintenance and washing tips on the fabric tab of the color chart. Use: Careful use is advised as they can be torn or cut.

THE LEATHERS

Cleaning: Clean with a damp white cloth soaked in water only. Use quality leather cleaning products by carefully following the instructions of the cleaning product manufacturer. If in doubt, it is recommended to test the product on a part hidden from view to verify the result, waiting at least 24 hours for any problems to arise.

Use: Remember that the skin is a delicate material therefore it is recommended to take care during use.

PLASTICS

Cleaning: Plastic surfaces should generally be cleaned with a damp, soft cloth soaked in water. It is not recommended to use dry cloths, which, when rubbed, could electrostatically charge the plastic surface, attracting dust. For more stubborn stains, you can dilute liquid neutral soap in water in moderation.

Absolutely avoid using acetone, trielin, ammonia, or detergents that contain even a small amount of these detergents because they can dull the shine of surfaces.

Avoid all abrasive substances, such as detergent powders, abrasive pastes, scouring pads, or rough sponges, absolutely.

Use: Avoid dragging objects that can line the material onto surfaces. Also remember, that plastic materials cannot withstand direct heat sources on the surface

METALS

Cleaning: Both steel or aluminum metal surfaces, as well as painted surfaces, should be cleaned with a damp, soft cloth soaked in hot water. For more stubborn stains, you can dilute liquid neutral soap in water in moderation. Always dry after cleaning with a soft cloth or chamois leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other harsh detergents. It is not recommended to use abrasive pastes, scouring pads, and abrasive sponges that can scratch metal surfaces. Use: Watch out for stains on foods such as coffee, cola, fruit juices that can leave permanent stains on surfaces

WARRANTY

QUINTI guarantees that the products will maintain their characteristics for 6 years from delivery, without prejudice to normal wear and tear and provided that they are used according to the instructions provided. QUINTI will replace any product found to be non-compliant with the said warranty without incurring any other liability whatsoever. The application of the warranty on components, external accessories or materials supplied by the buyer and applied to the products for the purpose of personalizing them is excluded. For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

All sessions offered are SAFE according to the provisions of EU Regulation 2023/988, on General Product Safety (GPSR), strengthened by UNI EN certifications.

The company does not hold itself liable if it is misused (Standing up or using products such as ladders and swings that could compromise the operation and safety of the user. To lift or move the product grip firmly on the supporting structure. The product must not be subjected to off-center loads, it is designed to be used under normal conditions of support on 4 legs or on the base).