Sugar Net





SEAT & BACKREST

Backrest: black or white polypropylene load-bearing structure, equipped with an adjustable lumbar support covered in Goal New type soft membrane. Optional adjustable padded and covered headrest or fixed in soft polyurethane

Seat: Made with a high-strength polypropylene interior with 2 steel bars inserted inside. Padding in Non-deformable polyurethane rubber thickness 50 mm. Double-stitched and lined.

ARMRESTS

- o Fixed black or white armrests
- o Height-adjustable arms in black or white Nylon
- Adjustable 3D armrests with soft polyurethane pad available in both black and white with black pad

MECCANICA

SUGAR NET has a **Syncron** in black aluminum. Seat height adjustment, synchronized seat backrest tilt adjustment with 4-position lockable shock absorber system. Backrest swing angle 20° seat swing 6.5° . Voltage regulation oscillation by handwheel. Seat translator



- 1. Seat height adjustment
- 2. Free back tilt
- 3. 5 swing positions lockable
- 4. Voltage adjustment flyer
- 5. Seat slide (Optional)



BASE

It's available with 3 different type of bases:

"LOOP" 5 polish aluminum spokes on castors [d. 680 mm] "LOOP" a 5 black PP spokes on castors Nero [d. 680 mm]

2001 a 5 black 11 spokes on easters (c. 000 mm)

Standard black double tread nylon wheels with diameter 65mm

"TREND" 5-spokes on wheels in white polypropylene [d. 680 mm]

Standard black double tread nylon wheels with diameter 65mm Optional with the same fixing pin diameter diam 11mm:

- O Wheeled wheels, black (R06) or grey with chrome sump (R07)
- o Black wheeled wheels and self breaking (R06A),
- o Rubberized wheels "pole" with central hole
- Black nylon feet (R08)

Measures	Seat height	Total height	Width	Depth
cm	45/55	102/112	68/48	68/43

Product certificate

The seat far exceeds the minimum requirements of DL 626/94, and DL.81. Complies with EN1335A and 1IM approved - CAM declaration.













Disassembly

All products have been designed in such a way as to allow them to be assembled at the end of their useful life, so that their parts and components can be reused, recycled or recovered for energy purposes.

Warranty & safety

QUINTI guarantees that the products will maintain their characteristics for 6 years from delivery, without prejudice to normal wear and tear and provided that they are used according to the instructions provided. QUINTI will replace any product found to be non-compliant with the said warranty without incurring any other liability whatsoever. E' excluding the application of the warranty on external components, accessories or materials supplied by the buyer and applied to the products for the purpose of personalizing them. For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

All sessions offered are SAFE according to the provisions of EU Regulation 2023/988, on General Product Safety (GPSR), strengthened by UNI EN certifications.

The company does not hold itself liable if it is misused (Standing up or using products such as ladders and swings that could compromise the operation and safety of the user. To lift or move the product grip firmly on the supporting structure. The product must not be subjected to off-center loads, it was designed to be used under normal conditions of support on 4 legs or on the base).

Use & maintenance

For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

THE FABRICS

Cleaning: See the maintenance and washing tips on the fabric tab of the color chart. Use: Careful use is advised as they can be torn or cut.

THE LEATHERS

Cleaning: Clean with a damp white cloth soaked in water only. Use quality leather cleaning products by carefully following the instructions of the cleaning product manufacturer. If in doubt, it is recommended to test the product on a part hidden from view to verify the result, waiting at least 24 hours for any problems to arise.

Use: Remember that the skin is a delicate material therefore it is recommended to take care during use. METALS

Cleaning: Both steel or aluminum metal surfaces, as well as painted surfaces, should be cleaned with a damp, soft cloth soaked in hot water. For more stubborn stains, you can dilute liquid neutral soap in water in moderation. Always dry after cleaning with a soft cloth or chamois leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other harsh detergents. It is not recommended to use abrasive pastes, scouring pads, and abrasive sponges that can scratch metal surfaces. Use: Watch out for stains on foods such as coffee, cola, fruit juices that can leave permanent stains on surfaces

Sugar Net



Upholsteries

LASER
CATEGORY 2

560 gr/mtl 100% Poliestere FR

Classe 1

80.000+/- 10% cicli Maltindale

ECOPELLE CATEGORY 2

630 g/lin.m

83% PVC 17%Sintetico

Classe 1

30.000 +/- 10% cicli Maltindale

JET

CATEGORY 3 365+/- 5% g/lin.m

365+/- 5% g/lin.m 100% Poliestere FR

Classe 1

80.000+/- 10% cicli Maltindale

ONE RECICLE CATEGORY 3

525 gr/mt2 100% recycled poliester

CLASSE 1IM 100.000 CICLI

LYRA
CATEGORY 3

550 g/lin.m 100% Poliestere Classe 1

60.000 +/- 10% cicli Maltindale

CHILI CATEGORY 3

470 gr/mtl

100% post-consumer recycled polyester

- 60.000 +/- cicli Maltindale

DREAM
CATEGORY 3

375gr/mtl

100% Poliestere tinto in massa melange effetto bouclè

OEKO TEST

Classe1 - 100.000 +/- cicli Maltindale

MELANGE CATEGORY 3

390 g/lin.m 100% Trevira CS Classe 1

RETE GABRIEL

100% Poliestere

510 g/lin.m

Classe 1

80.000 +/- 10% cicli Maltindale

70.000 +/- 10% cicli Maltindale

VELOURS CATEGORY 3

611 gr/mtl 100% Poliestere

Oeko test

50.000 +/- 10% cicli Maltindale

ECOPELLE SOUL CATEGORY 3

760 gr/mt2

Superficie 100% POLIURETANO, Base Poliestere 85%,17% Cotone EN1021-1/BS5852 PART 1 >100 000 FN ISO 5470-2

COCOON CATEGORY 5

980 gr/mtl

43% viscosa 33% cotone 24% li-pl 35.000 +/- 10% cicli Maltindale

LANA
CATEGORY 5

500 gr/mt2

75% Lana, 25% poliammide

Classe 1

100.000 cicli Maltindale

GLAMOUR CATEGORY 5

700 g/lin.m

100% Poliestere Recycled

EN 1021-1/2

80.000 % cicli Maltindale

TECHNICOLOUR Invadral CATEGORY 5

430 g/lin. M

100% new English wool, worsted

80.000 % cicli Maltindale

Ecolabel Classe 1

MAIN LINE cambra CATEGORY 5

437 g/lin.m

75% Lana Vergine, 25% Lino Classe 1, Ecolabel 50.000 +/- cicli Maltindale

PELLE

CATEGORY 5/6

620 g/lin.m 100% Pelle bovina Classe 1. EN 1021-1/2

RETE NEW GOAL 350 g/lin.m 100% Poliestere

Classe 1

100.000 +/- 10% cicli Maltindale

PELLE PREMIUM UP/ELEGANCE

CATEGORY 7

100% Pelle bovina Primo fiore Spessore 1,2/1,4 mm EN1021-1/2

MONOCHROME SETT cambra CATEGORY 7

437 g/lin.m

75% Lana Vergine, 25% Lino

Classe 1, Ecolabel 50.000 +/- cicli Maltindale

BOUCLET RUBELLI
CATEGORY 7

860 g/lin.m

40% PC, 25%PL,20%VI, 15% CO Classe 1, EN 1021-1/2 50.000 % cicli Maltindale

VELLUTO DECONTRACTE' HUBELLI

CATEGORY 7

590 g/lin.m

19% CO, 61% PC,10% PL, 10%VI 40.000 % cicli Maltindale

HORO (41941)

CATEGORY 7

495 g/lin.m

44%PL 29%CO 24%JU 3%PC 30.000 % cicli Maltindale

PELLE SETA

CATEGORY 8

100% Pelle bovina SPESSORE1,8-2 mm Primo fiore CONCIA ALL'ANILINA

EN1021-1/2

ZERO

CATEGORY 8

750g/lin.m

65% CO, 20% PAN, 15% PES 70.000 % cicli Maltindale