PAT Quinti



SHELL

Available in three variants:

• 6 mm thick embossed polypropylene monocoque, with soft lines and no edges. Available colors:



Oak wood monocoque with beveled profile available in finishes



• Wooden monocoque padded with polyurethane rubber 3 cm thick and covered. Double-stitched and horizontal topstitching "STRIPE" packaged. The fabric is glued to the rubber to prevent wrinkling over time during use.



PAT

Quinti^{*}

FRAME



DIMENSIONS

1. Armchair 4 legs frame	L52/44P 54/40 H78/44	8. Armchair 4 PP spokes	L67/44 P 67/40 H 76-86/44-52
2. Armchair rod frame	L52/44 P 54/40 H78/44	9. Armchair with Leggera 4 spokes base	L70/44 P 70/40 H81/90-47/56
3. Armchair rod frame NEW	L52/44 P 54/40 H78/44	10. Armchair with Punta/Trend 5 spokes base	L70/44 P 70/40 H81/90-47/56
4. Armchair 4 wooden legs	L52/44 P 54/40 H78/44	11. Armchair with 4 wooden spokes base	L70/44 P 70/40 H78/45
5. Armchair with 4 legs and arms	L52/44 P 54/40 H78/44	12. 4 legs stool	L46/44 P 52/40 H109/72
6. Armchair with 4 legs, arms and writing table	L57/44 P 54/40 H78/44	13. 5-spoke base stool and footrest ring	L70/44 P 70/40 H90/109-55/72
7. Armchair inverted cantilever no arms	L56/44 P 58/40 H78/44	14. 5-spoke base stool and integrated footrest	L70/44 P 70/40 H90/109-55/72

- 4-leg metal frame (16 mm diameter) available with integrated armrests and tablet, in the finishes:
- Chrome
- Standard black painted
- Standard white painted
- Round frame/ NEW round (11mm diameter) with nylon feet in the finishes:
- Chrome
- Standard black painted
- Standard white painted
- 4-legged frame in painted FSC wood in the finishes:
- Natural
- Moka
- Walnuts
- Black open pore
- Lightweight 4-spoke base in polished aluminum (diameter 70 cm) swivel (with elevation) available with wheels or feet.
- 4-spoke black polypropylene base (swivel (with elevation) available with wheels or feet.
- Trend base 5 spokes on wheels (diameter 68 cm) rotatable (with elevation) available in:
- Polished aluminum
- Black polypropylene
- White polypropylene
- 4-spoke rotating base (without elevation) in painted oak wood
- Natural
- Moka
- Walnuts
- Black open pore
- Metal cantilever frame made of 20 mm diam tubular, with or without armrests in the finishes:
- Standard white painted
- Standard black painted
- Stool frame 4 legs made of tubular diam 16 mm in the finishes:
- Standard white painted
- Standard black painted

PAT



• Stool frame with footrest ring and 5-spoke base (diameter 68 cm) on feet available in:

- -glossy aluminum
- -white polypropylene
- -black polypropylene

• 2, 3 or 4 seat bench structure with white painted metal trestle leg (pair of polished aluminum legs available). The bodies are hooked with fixing omega and plate under seat on beam 80x40 mm painted white or aluminum grey







1. DIM 2P L120/44 P 61/4 H78/42

2. DIM 3P L175/44 P 61/4 H78/42

3 DIM 4P I 238/44 P 61/4 H78/42

ACCESSORIES

Chrome wire armrests Wooden armrests Alignment hook Chair trolley

SEAT CERTIFICATE

- CL1 fire reaction approval
- FSC
- ReMade plastic

Disassembly

All products have been designed in such a way as to allow them to be assembled at the end of their useful life, so that their parts and components can be reused, recycled or recovered for energy purposes.

Warranty & safety

QUINTI guarantees that the products will maintain their characteristics for 6 years from delivery, without prejudice to normal wear and tear and provided that they are used according to the instructions provided. QUINTI will replace any product found to be non-compliant with the said warranty without incurring any other liability whatsoever. E' excluding the application of the warranty on external components, accessories or materials supplied by the buyer and applied to the products for the purpose of personalizing them. For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

All sessions offered are SAFE according to the provisions of EU Regulation 2023/988, on General Product Safety (GPSR), strengthened by UNI EN certifications.

The company does not hold itself liable if it is misused (Standing up or using products such as ladders and swings that could compromise the operation and safety of the user. To lift or move the product grip firmly on the supporting structure. The product must not be subjected to off-center loads, it was designed to be used under normal conditions of support on 4 legs or on the base).

Use & maintenance

For optimal product maintenance and to maintain the characteristics of the materials from which they are made unchanged, some simple care is necessary.

THE FABRICS

Cleaning: See the maintenance and washing tips on the fabric tab of the color chart. Use: Careful use is advised as they can be torn or cut.

THE LEATHERS

Cleaning: Clean with a damp white cloth soaked in water only. Use quality leather cleaning products by carefully following the instructions of the cleaning product manufacturer. If in doubt, it is recommended to test the product on a part hidden from view to verify the result, waiting at least 24 hours for any problems to arise.

Use: Remember that the skin is a delicate material therefore it is recommended to take care during use.

METALS

Cleaning: Both steel or aluminum metal surfaces, as well as painted surfaces, should be cleaned with a damp, soft cloth soaked in hot water. For more stubborn stains, you can dilute liquid neutral soap in water in moderation. Always dry after cleaning with a soft cloth or chamois leather. Do not use creams and pastes to clean steel, do not use chlorine, do not use bleach and other harsh detergents. It is not recommended to use abrasive pastes, scouring pads, and abrasive sponges that can scratch metal surfaces. Use: Watch out for stains on foods such as coffee, cola, fruit juices that can leave permanent stains on surfaces



Upholsteries

LASER CATEGORY 2

Classe 1

560 gr/mtl 100% Poliestere FR

80.000+/- 10% cicli Maltindale

ECOPELLE CATEGORY 2

630 g/lin.m

83% PVC 17% Sintetico

Classe 1

30.000 +/- 10% cicli Maltindale

JET CATEGORY 3 365+/- 5% g/lin.m

100% Poliestere FR

Classe 1

80.000+/- 10% cicli Maltindale

ONE RECICLE CATEGORY 3

525 gr/mt2 100% recycled poliester CLASSE 1IM 100.000 CICLI

LYRA CATEGORY 3

550 g/lin.m 100% Poliestere Classe 1

60.000 +/- 10% cicli Maltindale

CHILI CATEGORY 3

470 gr/mtl 100% post-consumer recycled polyester

- 60.000 +/- cicli Maltindale

DREAM
CATEGORY 3

375gr/mtl

100% Poliestere tinto in massa melange effetto bouclè

OEKO TEST

Classe1 - 100.000 +/- cicli Maltindale

MELANGE CATEGORY 3

390 g/lin.m 100% Trevira CS Classe 1

80.000 +/- 10% cicli Maltindale

VELOURS CATEGORY 3

611 gr/mtl 100% Poliestere Oeko test

50.000 +/- 10% cicli Maltindale

ECOPELLE SOUL CATEGORY 3

760 gr/mt2

Superficie 100% POLIURETANO, Base Poliestere 85%,17% Cotone EN1021-1/BS5852 PART I >100.000 EN ISO 5470-2

COCOON CATEGORY 5

980 gr/mtl

43% viscosa 33% cotone 24% li-pl 35.000 +/- 10% cicli Maltindale

LANA

CATEGORY 5 500 gr/mt2

75% Lana, 25% poliammide

Classe 1

100.000 cicli Maltindale

GLAMOUR CATEGORY 5

700 g/lin.m 100% Poliestere Recycled

EN 1021-1/2

80.000 % cicli Maltindale

TECHNICOLOUR kvadral

CATEGORY 5

430 g/lin. M

100% new English wool, worsted

80.000 % cicli Maltindale

Ecolabel Classe 1

MAIN LINE cambra CATEGORY 5

437 g/lin.m

75% Lana Vergine, 25% Lino

Classe 1, Ecolabel

50.000 +/- cicli Maltindale

PELLE CATEGORY 5/6

620 g/lin.m 100% Pelle bovina Classe 1, EN 1021-1/2 PELLE PREMIUM UP/ELEGANCE

CATEGORY 7

100% Pelle bovina Primo fiore Spessore 1,2/1,4 mm EN1021-1/2

MONOCHROME SETT cambra

CATEGORY 7

437 g/lin.m

75% Lana Vergine, 25% Lino Classe 1, Ecolabel 50.000 +/- cicli Maltindale

BOUCLET RUBELLI
CATEGORY 7

860 g/lin.m

40% PC, 25%PL,20%VI, 15% CO Classe 1, EN 1021-1/2 50.000 % cicli Maltindale

VELLUTO DECONTRACTE' RUBELLI CATEGORY 7

OO adin m

590 g/lin.m

19% CO, 61% PC,10% PL, 10%VI 40.000 % cicli Maltindale

HORO (41981)

CATEGORY 7

495 g/lin.m

44%PL 29%CO 24%JU 3%PC 30.000 % cicli Maltindale

PELLE SETA CATEGORY 8

100% Pelle bovina SPESSORE1,8-2 mm Primo fiore CONCIA ALL'ANILINA

EN1021-1/2

ZERO CATEGORY 8

750g/lin.m

65% CO, 20% PAN, 15% PES 70.000 % cicli Maltindale