

**BESTRAP R80 HE (UNI EN 13246 Type 3.1)**

LARGHEZZA Width (mm)	SPESSORE Thickness (mm)	SUPERFICIE Surface	CONFEZIONAMENTO Wound	RM Mpa	m/Kg	ALLUNGAMENTO [A100%] Elongation [A100%]
19	0,80	L/B/BP/ZP	RW/OW/JC	≥ 750	8,4	min 12
25	0,80	L/B/BP/ZP	RW/JC	≥ 750	6,4	min 12
	0,90	B/BP/ZP	RW/JC	≥ 750	5,7	min 12
32	0,80	L/B/BP/ZP/ZC	RW/JC	≥ 750	5,0	min 12
	0,90	B/BP/ZP/ZC	RW/JC	≥ 750	4,4	min 12

SUPERFICIE Surface	
L	Lucida Bright
B	Blu Blue
BP	Laccata Nera Black Painted
ZP	Zincata Verniciata Zinc Painted
ZC	Zincata a caldo Hot Galvanized

CONFEZIONAMENTO Wound	
RW	Monospira Ribbon
OW	Oscillata Oscillated
JC	Jumbo 200 Jumbo 200
	Jumbo 400 Jumbo 400
	Jumbo 1000 Jumbo 1000