



MODEL

Protect 200 (NV200)

Wall mountable or countertop unit,
1-NanoStrike coil, supplied with 1.6m power
cord (minimum length).

CONSTRUCTION + COLOUR

Precision-cut fabricated metal casing in a white
anti-bacterial powder coat finish

DIMENSIONS

283 mm (h) x 132 mm (w) x 108 mm (d)
11.1" (h) x 5.2" (w) x 4.3" (d)

WEIGHT

3.4kg | 7.5lbs

OPERATING CONDITIONS

10-35°C | 50-95°F, 10-75% Relative Humidity

SHIPPING/STORAGE CONDITIONS

5-50°C | 41-122°F, Maximum 95% Relative
Humidity

ELECTRICAL RATING

Single Phase, 100-130 VAC | 220-240 VAC, 50-60 Hz
Fuse Rated at 250 VAC, 3 Amps, Listed

POWER CONSUMPTION RANGE*

100-130 VAC model:
12.9W – 21.8W

ELECTRICAL CONNECTION

Switched and fused with a grounded, moulded power cord

FAN AIR FLOW VOLUME

80 m³/hr | 47 CFM

NOISE LEVEL*

35 dB

QUALITY STANDARDS

Manufactured under ISO 9001, ISO 14001
& OHSAS 45001

GLOBAL CERTIFICATIONS

IEC 60601-1
IEC 60601-1-2
IEC 60335-1
IEC 60335-2-65
Conforms to Low Voltage Directive (LVD) 2014/35/EU
CE
UL 867
FCC
CSA C22.2 NO. 187:20
CARB
FCC
China Disinfection WS/T 648
KCC
JQA S-Mark



* Power consumption depends on voltage and frequency of network in particular country
* Measured at the unit.