



## MODEL

### WellAir Nano

Wall mountable or countertop unit,  
1-NanoStrike coil, supplied with 1.6m power  
cord (minimum length).

## CONSTRUCTION + COLOUR

Precision-cut fabricated metal casing in a silver  
anti-bacterial powder coat finish

## DIMENSIONS

283 mm (h) x 132 mm (w) x 108 mm (d)  
11.1" (h) x 5.2" (w) x 4.3" (d)

## WEIGHT

3.4kg | 7.5lbs

## OPERATING CONDITIONS

10-35°C | 50-95°F, 10-75% Relative Humidity

## SHIPPING/STORAGE CONDITIONS

5-50°C | 41-122°F, Maximum 95% Relative  
Humidity

## ELECTRICAL RATING

Single Phase, 100-130 VAC | 220-240 VAC, 50-60 Hz  
Fuse Rated at 250 VAC, 3 Amps, Listed

## POWER CONSUMPTION RANGE\*

100-130 VAC model:  
12.9W – 21.8W

## ELECTRICAL CONNECTION

Switched and fused with a grounded, moulded power cord

## FAN AIR FLOW VOLUME

80 m<sup>3</sup>/hr | 47 CFM

## NOISE LEVEL\*

35 dB

## QUALITY STANDARDS

Manufactured under ISO 9001, ISO 14001 & OHSAS 45001

## GLOBAL CERTIFICATIONS

IEC 60601-1  
IEC 60601-1-2  
IEC 60335-1  
IEC 60335-2-65  
Conforms to Low Voltage Directive (LVD) 2014/35/EU  
CE  
UL 867  
FCC  
CSA C22.2 NO. 187:20  
CARB  
China Disinfection WS/T 648  
KCC  
JQA S-Mark

\* Power consumption depends on voltage and frequency of network in particular country

\* Measured at the unit.