



MODEL Nano

Wall mountable or countertop unit, 1-NanoStrike coil, supplied with 6.6 ft | 1.6 m power cord (minimum length).

CONSTRUCTION + COLOR

Precision-cut fabricated metal casing in a silver anti-bacterial powder coat finish

DIMENSIONS

11.1" (h) × 5.2" (w) × 4.3" (d)
283 mm (h) × 132 mm (w) × 108 mm (d)

WEIGHT

7.5lbs | 3.4 kg

OPERATING CONDITIONS

50-95°F | 10-35°C, 10-75% Relative Humidity

SHIPPING/STORAGE CONDITIONS

41-122°F | 5-50°C, Maximum 95% Relative Humidity

ELECTRICAL RATING

Single Phase, 100-130 VAC 1220-240 VAC, 50-60 Hz
Fuse Rated at 250 VAC, 3 Amps, Listed

POWER CONSUMPTION RANGE

100-130 VAC model
12.9W- 21.8W

ELECTRICAL CONNECTION

Switched and fused with a grounded, molded power cord

FAN AIR FLOW VOLUME

47 CFM | 80 m³/hr

NOISE LEVEL

35dB

QUALITY STANDARDS

Manufactured under ISO 9001, ISO 14001
& OHSAS 45001

GLOBAL CERTIFICATIONS

IEC 60601-1
IEC 60601-1-2
IEC 60335-1
IEC 60335-2-65
Conforms to Low Voltage Directive (LVD) 2014/35/EU
CE
UL867
FCC
CSA C22.2 NO. 187:20
CARB
FCC
China Disinfection WS/T 648
KCC
JQAS-Mark



* Power consumption depends on voltage and frequency of network in particular country.
* Measured at the unit.