

Waterproof Junction Box Coupling



JBX-WP-3P
JBX-WP-4P
JBX-WP-5P



JBX-WP-6P

Series

JBX-WP-3P
JBX-WP-4P
JBX-WP-5P
JBX-WP-6P

JBX-WP-3P

- SO CORD 3 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR
- VOLTAGE RATING: 450V
- CURRENT RATING: 26A
- MIN WIRE SIZE OD: .5-2.5mm, 10-14mm
- UL/ROHS/TUV/UL94-V2/CE

JBX-WP-4P

- SO CORD 4 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR
- VOLTAGE RATING: 450V
- CURRENT RATING: 26A
- MIN WIRE SIZE OD: .5-2.5mm, 10-14mm
- UL/ROHS/TUV/UL94-V2/CE

JBX-WP-5P

- SO CORD 5 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR
- VOLTAGE RATING: 450V
- CURRENT RATING: 26A
- MIN WIRE SIZE OD: .5-2.5mm, 10-14mm
- UL/ROHS/TUV/UL94-V2/CE

JBX-WP-6P

- SO CORD 6 WIRE IP68 SCREWLESS QUICK WIRING CONNECTOR
- VOLTAGE RATING: 450V
- CURRENT RATING: 26A
- MIN WIRE SIZE OD: .3-.5mm, 9-12mm
- UL/ROHS/TUV/UL94-V2/CE

Specs and model numbers are subject to change with or without notice. Customization of product is available.