



SnapTrim-Line: 2" Gimbal Downlights

Canless Series



Detail Specifications:

- Finish: White Finish
- IP54 Wet Location Rated
- 8W 600 Lumens
- Beam Angle: 38° standard
- Chip: COB Chip, R9 >50, CRI >90
- 3 Step MacAdam Ellipses
- Operating Temperature: -40° - 114° F
- Lens: Clear, non-yellowing
- Average life (L70) of 50,000 hours

Applications:

- Accent Lighting
- Displays, Cabinets, Bars
- Residential & Multifamily

Product Information:

- Standard white round trim included
- Metal housing and trim for better heat dissipation
- Optional emergency backup available: delivers full lumens in EM mode up to 25W
- SnapTrim Canless: Spring clips with remote j-box eliminates can

Driver Options:

- 120V Triac Dimmable
- Built in 2.5Kv Surge Protector
- Flicker Free

Mounting & Installation:

- Cut Out Dimension: 2"
- Optional new construction plate available
- This fixture does not fit into a recessed can
- No housing needed in remodel applications, tension clips mount into 1/2" to 1.5" thick ceiling
- Can be removed from below the ceiling for service or replacement
- Pre-wired junction box with circuit wiring built in (3 in/ 3 out)

Certifications:

- ETL Listed for USA and CA
- CA Title 24 JA8-2022 CEC Listed
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017
- IC Rated and ASTM-E283 Air-Tight

Series

Emergency

LED-DLJBX-ADJ-2-5W-5CCT-WH
LED-DLJBX-ADJ-2-5W-27K
LED-DLJBX-ADJ-2-5W-40K
LED-DLJBX-ADJ-2-5W-50K

(Blank)
No Emergency
Backup
EMB
Emergency
Backup

Optional Accessories (Order Separately)

New Construction Plates

CUNV-NC-ICAT-7H
Universal Plate
with Hanging Bars
CUNV-JBX-RI-XL
Universal Rough In
Plate Extra Long

Extension Cables

JBX-EXT-6'-2PIN
6' Extension
JBX-EXT-10'-2PIN
10' Extension
JBX-EXT-12'-2PIN
12' Extension


Emergency Backup ¹ (field install)

LED-EMB-25W-HV
-0/10V-2P
Up to 24W fixtures


1. Trims are field changeable.
For brushed nickel finish it is
recommended to use the black
body fixtures

Specs and model numbers are subject to change with or without notice.

FEATURES




DIMENSIONS




SnapTrim-Line: 2" Gimbal Downlights

Canless Series

ACCESSORIES



CUNV-NC-ICAT-7H
Universal Pre-Mounting Plate
13 7/8" x 15 1/8"



CUNV-JBX-RI-XL
7" x 26"



JBX-EXT
6' / 10' / 12' Extension Cable



LED-EMB-25W-HV-0/10V-2P

	Model	Voltage	Watts	Lumens	Color	CRI
	LED-DLJBX-ADJ-2-5W-5CCT-WH	120V	5w	350	27/30/35/40/50K	>90
	LED-DLJBX-ADJ-2-5W-27K	120V	5w	350	2700k	>90
	LED-DLJBX-ADJ-2-5W-40K	120V	5w	350	4000k	>90
	LED-DLJBX-ADJ-2-5W-50K	120V	5w	350	5000k	>90

CONSTRUCTION PLATES

Accessory	Description
CUNV-NC-ICAT-7H	1" 2"3" 3.5" 4" 5" 6" Universal Pre-Mounting New Construction Plate
CUNV-JBX-RI-XL	Universal tough in plate (Extra Long)

EXTENSION CABLE

Accessory	Description
JBX-EXT-6'-2PIN	6" Extension Cable
JBX-EXT-10'-2PIN	10" Extension Cable
JBX-EXT-12'-2PIN	12" Extension Cable

EMERGENCY BACKUP

Accessory	Description
LED-EMB-25W-HV-0/10V-2P	Up to 24W fixtures

TESTED COMPATIBLE DIMMERS

Other dimmers may be compatible but have not been tested.
Please contact us for more information.

TRIAC/ELV Dimmers

Lutron	Leviton	Legrand	Cooper
AYCL-153P	6633	ADTP703TU	9540
DV-600PR	6674	H703PTW	DAL06P
DVCL-153P	6602		
MACL-153MH	IPL06		
MRF2-6CL			
D-600P			
NTELV-300P			
S-600P			
CT-600P			
CTCL-153P			
TG-600P			
TCCL-153P			