

### **Wall Mounted Sensor** x SILVAIR Enabled



		Ø4.5'
		04.5
	) /	
Ø3"		

Project:	Part #:
Type:	

**Sensors** 







S-WM-PIR-CUNV-SL allows for group level luminaire control and is equipped with PIR occupancy sensing. It utilizes a Bluetooth® Low Energy (BLE) mesh network. Commissioning can be set through the SILVAIR mobile app or desktop site.

## **Detail Specifications:**• Input Voltage: 120-277V • Operating Temperature: -4-104F°

- Finish: White180° detection
- Max Bluetooth Range: 100' line of sight
- Highly dependent on surrounding environment
- Bluetooth test recommended for range accuracy
- IP Rating: IP20 Dry Location

#### Applications:

- ommercial & Industrial
- 0-10V Dimmable Fixtures

#### **Product Information:**

- PIR motion sensor: Ideal for indoor environments with clear lines of sight to the area of interest. Detects warm objects, good for high vibration, areas of metal.
- Magnetic Reset: touch the top part of the sensor for 5 seconds
- Include parameter profiles, dimming control, real-time sensor feedback
   View our SILVAIR guide for full features

# Mounting & Installation: • Single-gang wall box • 30ft @ 4ft mounting height • Connect up to 3,000 devices on a zone

#### **Certifications:**

- UL Listed for USA and CA
   DLC NLC Listed ID NSLVR23CNTRL
- Bluetooth

- Approved for CA T24
  5 Year Limited Warranty
  FCC CFR 47, GCC Part 15, Subpart B:2017

S-WM-PIR-CUNV-SL