

Project: _____
 Part#: _____
 Type: _____



Trimless Surface Mount

The NEW EnVision LED Trimless Surface Mount is ultra thin, easy to install, and ideal for any residential or commercial recessed setting. The fixture has various mounting options making it easy to retrofit an existing fixture or install in a new construction setting. With our elegant and minimal design, which blends seamlessly into the ceiling, these trimless surface mounts are sure to turn some heads.

Detail Specifications:

- Wet Location Rated
- CRI 90 LED Chip, R9>50
- 120V Driver
- 100° Beam Angle
- Operating Temperature: 0°F ~ +113°F
- PF >0.9
- Triac and ELV Dimmable Down to 5%

Applications:

- Residential or Commercial Lighting
- New Construction or Remodel Use
- General Recessed Lighting

Mounting:

- Compatible with 30 or 40 J-Box (req's 0.7" room in box)
- Option recessed can converter accessories available: (5" works in 4" can / 7", 9", 11" works in 6" can)

Certifications:

- ETL Listed for USA and CA
- Energy Star
- IC Rated and ASTM-E283 Air-Tight
- CA Title 24 JA8-2019 CEC Listed
- FCC CFR 47, FCC Part 15, Subpart B:2017
- 5 Year EnVision LED Limited Warranty

Product Information:

- Stocked in 30K: other CCT available with lead time
- Di-cast aluminum housing for better heat dissipation
- Available in white, black, brushed nickel finish
- Closet Rated according to NEC Section 410.6 & 410.8
- Optional Emergency Backup Available: delivers full lumens in EM mode
- L70 @ 50,000 Hours lumen maintenance

What's Included:

- LED Fixture
- Junction Box Mounting Plate
- Mounting Screws
- Installation Guide
- Recessed can converter available for separate purchase



1	Product	2	Size/Wattage	3	Color	4	Finish	5	Warranty
LED-TSM	Trimless Surface Mount	5-12W	5" - 12W (850 Lumens)-71lm/W	30K	3000K	WH	White	5YR	5 Years (Incl.)
		5-15W	5" - 15W (1,000 Lumens)-67lm/W			BLK	Black		
		7-15W	7" - 15W (1,000 Lumens)-67lm/W			BN	Brushed Nickel		
		9-18W	9" - 18W (1,300 Lumens)-72lm/W						
		11-20W	11" - 20W (1,500 Lumens)-75lm/W						

Specs and model numbers are subject to change with or without notice

FEATURES**Flawless Brilliance**

Precisely optimized LED array delivers smooth, uniform illumination with no visible dark spots

Dimming Capability

This fixture is compatible with industry standard TRIAC/ELV dimmers, being able to dim from 10% - 100%

Clearly Different

Specilized lens transmit clear, beautiful light with a subtle diffusion

Designed to Disappear


Extends just 0.6" below the ceiling plane to minimize visual profile

Seamless Integration


Elegant, minimal design blends seamlessly into the ceiling



ACCESSORIES



TSM-7R-EMB-UNV
TSM-9R-EMB-UNV



TSM-7R-EMPTY-UNV
TSM-9R-EMPTY-UNV



LED-EMB-25W-HV-0/10V-2P

Model	Voltage	Watts	Lumens	Color	CRI
LED-TSM-5R-12W-30K-WH	120V	12w	850	3000K	>90
LED-TSM-7R-15W-30K-WH	120V	15w	1,000	3000K	>90
LED-TSM-9R-18W-30K-WH	120V	18w	1,300	3000K	>90
LED-TSM-11R-20W-30K-WH	120V	20w	1,500	3000K	>90

EMERGENCY BACKUP

Accessory	Description
TSM-7R-EMB-UNV	7" Surface mount pancake EMB
TSM-7R -EMB-EMPTY-UNV	7" Empty surface mount pancake EMB
TSM-9R -EMB-UNV	9" Surface mount pancake EMB
TSM-9R-EMB-EMPTY-UNV	9" Empty surface mount pancake EMB
LED-EMB-25W-HV-0/10V-2P	Remote EMB for fixtures up to 25W

TESTED COMPATIBLE DIMMERS

Other dimmers may be compatible but have not been tested. Please contact us for more information.

Lutron
LUTRON PD-6WCL
LUTRON DVCL-153P
LUTRON CTCL-153P
LUTRON MACL-153M
LUTRON LECL-153