

Directional Retrofit Lamp

3-Power Selectable



The EnVision LED flat directional HID replacement lamp allows the end user to retrofit existing shoebox, wall pack, and flight light housings. The lamp includes an internal driver with a 6kV surge protector inside.

Detail Specifications

- IP Rating: IP64 Wet Location
- Beam Angle: 120°
- Base: EX39
- CCT: 5000K standard (30,40,57k available custom order)
- Chip: SMD 2835, R9 >50, CRI >80
- Operating Temperature: -40° - 122° F
- Average life (L70) of 50,000 hours

Applications:

- Outdoor Lighting
- HID Lamp Replacement
- Shoebox, Wall Pack, Flood Light Retrofit
- Residential, Commercial and Industrial

Product Information:

- Aluminum housing for heat dissipation
- Suitable for use in existing fixtures
 - Ballast bypass required
- Connect directly to 120-277V power
- Instant-On to full brightness

Driver Options:

- 120-277V
- 0-10V Dimmable
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz

Mounting & Installation:

- EX39 socket
- Ballast bypass required

Certifications:

- UL Listed for USA and CA
- DLC Listed
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017

3P54

WATT	LUMENS
36	4,140
45	5,175
54	6,210

3P115

WATT	LUMENS
75	8,625
95	10,925
115	13,225

Series

LED-FLL-3P54-50K-EX39

54/45/36w

LED-FLL-3P115-50K-EX39

115/95/75w

Specs and model numbers are subject to change with or without notice.

FEATURES



DIMENSIONS

