




Low Voltage: Path Lights (Shade)

Aluminum – Architectural Models



PL-H-ALM-BZ-1

PL-H-ALM-BL-1

PL-H-ALM-BZ-2

PL-H-ALM-BL-2

PL-H-ALM-BZ-3

PL-H-ALM-BL-3



Detail Specifications:

- Finish: Bronze or Black
- Housing: Aluminum
- Lamp Type:
 - G4 Bulbs 12V (not included)
 - 35W Halogen Max
 - LED bulbs available
- IP Rating: Wet Location IP65
- Lens: Clear glass

Applications:

- Landscape
- Walkways & Pathways
- Security Lighting
- Hospitality, Multi-Family
- Outdoor Corridors
- General Outdoor Lighting
- Residential, Commercial

Product Information:

- Heat resistant glass lens
- Water tight silicone ring for waterproofing
- Stem Options: 12" or 24" Height
- Shade Options: various options available
- Stem and shade sold separately
- Packaging: Retail color box
- Master Box Quantity:
 - Stems: 10pcs.
 - Shades: 10pcs.

Driver Options:

- Compatible with 12V Low Voltage Drivers

Mounting & Installations:

- Wire: 6' (72") SPT-1W 18 gauge wire lead
- Spike: 8.3" Non-metallic spike included
 - Optional brass spike available
- Solid aluminum pipe with 1/2" knuckle stem

Warranty:


- 1 Year Limited Warranty on Housing Defects

Aluminum Bronze Stem Options	Aluminum Bronze Shade Options	Aluminum Black Stem Options	Aluminum Black Shade Options	1 Bulb Options
PL-12-ALM-BZ-12V 12" Height PL-24-ALM-BZ-12V 24" Height	PL-H-ALM-BZ-1 Style 1 PL-H-ALM-BZ-2 Style 2 PL-H-ALM-BZ-3 Style 3	PL-12-ALM-BL-12V 12" Height PL-24-ALM-BL-12V 24" Height	PL-H-ALM-BL-1 Style 1 PL-H-ALM-BL-2 Style 2 PL-H-ALM-BL-3 Style 3	LED-G4WP-1.5W-SW 2700K LED-G4WP-1.5W-WW 3000K LED-G4WP-1.5W-CW 4000K LED-G4WP-2.5W-SW 2700K LED-G4WP-2.5W-WW 3000K LED-G4WP-2.5W-CW 4000K LED-G4WP-3.5W-SW 2700K LED-G4WP-3.5W-WW 3000K LED-G4WP-3.5W-CW 4000K


Optional Accessories on Page 3

Specs and model numbers are subject to change with or without notice. Customization of product is available.

FEATURES



DIMENSIONS






LED-G4WP-1.5W-SW
LED-G4WP-1.5W-WW
LED-G4WP-1.5W-CW

LED-G4WP-2.5W-SW
LED-G4WP-2.5W-WW
LED-G4WP-2.5W-CW

LED-G4WP-3.5W-SW
LED-G4WP-3.5W-WW
LED-G4WP-3.5W-CW



SM-1/2-BR-ORB **SM-1/2-BR-MBL** **SM-1/2-ALM-BZ** **SM-1/2-ALM-BL**



SM3-1/2-BR-ORB **SM3-1/2-BR-MBL** **STKC-1/2-BR-ORB** **STKC-1/2-BR-MBL**



PL-AT-1/2-ALM-BZ **PL-AT-1/2-ALM-BL** **STK-HD-1/2-BR**

Model	Voltage	Color
PL-12-ALM-BZ-12V	12V	Bronze
PL-24-ALM-BZ-12V	12V	Bronze
PL-12-ALM-BL-12V	12V	Black
PL-24-ALM-BL-12V	12V	Black

BULBS

Model	Voltage	Watts	Lumens	Color
LED-G4WP-1.5W-SW	12V AC/DC	1.5w	110	2700k
LED-G4WP-1.5W-WW	12V AC/DC	1.5w	110	3000k
LED-G4WP-1.5W-CW	12V AC/DC	1.5w	110	4000k
LED-G4WP-2.5W-SW	12V AC/DC	2.5w	210	2700k
LED-G4WP-2.5W-WW	12V AC/DC	2.5w	210	3000k
LED-G4WP-2.5W-CW	12V AC/DC	2.5w	210	4000k
LED-G4WP-3.5W-SW	12V AC/DC	3.5w	280	2700k
LED-G4WP-3.5W-WW	12V AC/DC	3.5w	280	3000k
LED-G4WP-3.5W-CW	12V AC/DC	3.5w	280	4000k

STAKE

Model	Voltage
STK-HD-1/2-BR	Brass Stake 10" Heavy Duty

SURFACE MOUNT

Model	Description
SM-1/2-BR-ORB	Brass Stake 10" Heavy Duty (Oil Rubber Bronze)
SM-1/2-BR-MBL	Brass 1/2" Surface Mount (Matte Black)
SM-1/2-ALM-BZ	Aluminum 1/2" Surface Mount (Bronze)
SM-1/2-ALM-BL	Aluminum 1/2" Surface Mount (Black)

TREE MOUNT

Model	Description
SM3-1/2-BR-ORB	Brass Stake 10" Heavy Duty (Oil Rubber Bronze)
SM3-1/2-BR-MBL	Brass 1/2" Surface Mount (Matte Black)

STAKE COVER

Model	Description
STKC-1/2-BR-ORB	Brass Stake Cover(Oil Rubbed Bronze)
STKC-1/2-BR-MBL	Brass Stake Cover(Matte Black)

PATH LIGHT COVER

Model	Description
PL-AT-1/2-ALM-BZ	Path Light Cover (Bronze)
PL-AT-1/2-ALM-BL	Path Light Cover (Black)