

VIVO-X8D8

DIGITAL PROCESSORS & MATRIXES

EclerPLEX Matrix 8x8 Analogue 8x8 Dante/AES67



PRODUCT OVERVIEW

VIVO-X8D8 is an EclerPLEX Host matrix with 8 analogue and 8 Dante/AES67 audio input ports, 8 analogue and 8 Dante/AES67 audio output ports, scalable thanks to two X-link ports. A BIO-X8 (or BIO-X8G) expansion unit can be connected to each X-link port. VIVO-X8D8, performing as a Host unit in an EclerPLEX project, can contain multiple projects running simultaneously and serve user panels to end users.

KEY FEATURES

- EclerPLEX ecosystem host matrix unit.
- 8 MIC / LINE analogue audio input ports (+48V Phantom selectable per port).
- 8 LINE analogue audio output ports.
- 8 Dante™/AES67 digital input ports (4 flows).
- 8 Dante™/AES67 digital output ports (4 flows).
- 8 GPI ports.
- 8 GPO ports.
- 1 microSD card slot (for the 4 players).
- 2 x X-link audio&control expansion ports (each port allows to locally connect an external BIO-X8 BIO-X8G expansion unit).
- Scalable up to a 32x32 audio matrix size, including:
 - 24x24 analogue audio ports (by adding 2x BIO-X8 or BIO-X8G units).
 - 24x24 GPIO ports (by adding 2x BIO-X8 or BIO-X8G units).
 - 8x8 digital audio ports (Dante™/AES67).
- 2x Ethernet (NET1 control, NET2 Control + Dante™/AES67).
- 1 x RS-232 control port.
- 1 x X" Colour TFT Display.
- Flexible processing structure (allows for custom-size matrix size matrices and custom-DSP power projects).
- Embedded EclerPLEX application that includes:
 - A Workspace, including multiple types of custom-size simultaneous projects running simultaneously, events, calendars, presets and more.
 - An editor, manager and server of User Control Panels
 - Scripting automation & control system.
 - 4 Internal SW audio players.
 - 2 Internal audio generators.
 - EclerCLOUD monitor and control native device.
 - Auto update feature.

APPLICATIONS

- Retail
- Corporate
- Sports & Wellness
- Hospitality

TECHNICAL SPECIFICATIONS

VIVO-X8D8




Digital Engine	
Processor	Quad core 64bits 1,5GHz
Audio Converters	
Sampling rate	48 kHz
Resolution	32 bit
Latency	<4ms
Frequency response	10Hz to 20kHz (-0,5 dB)
Dynamic range	ADC:115dB, DAC: 115dB
Analogue Audio Input Ports	
Number of input ports	8, MIC/LINE level
Connection type	Euroblock, 3-pin, balanced
Input sensitivity	-32,5 dBV to +18,5 dBV -30,3 dBu to +20,7 dBu
Input impedance	7k6 Ω (balanced), 3k8 Ω (unbalanced)
Max input level	18,5 dBV / 20,7dBu
Mic preamp EIN	<-129,5 dBV <-127,3 dBu
Dynamic range	Gain 0 dB: >110,2 dB Gain 21 dB: >109,5 dB Gain 42 dB: >105,5 dB Gain 51 dB: >99,5 dB
THD + Noise	Gain 0 dB & Vin 0 dBV: 0,0025% Gain 21 dB & Vin -21 dBV: 0,0026% Gain 42 dB & Vin -42 dBV: 0,0044% Gain 51 dB & Vin -51 dBV: 0,0085% Gain 0 dB & Vin +17 dBV: 0,0010% Gain 21 dB & Vin -4 dBV: 0,0015% Gain 42 dB & Vin -25 dBV: 0,0010% Gain 51 dB & Vin -34 dBV: 0,0015%
CMRR	>70dB typ (1kHz) >60 dB typ (20 Hz - 20kHz)
Phantom power	+48VDC, 7mA per input max
Analogue Audio Output Ports	
Number of output ports	8, LINE level
Connection type	Euroblock, 3-pin, balanced
Max output level	18,5dBV / 20,7dBu
Output impedance	300 Ω (balanced), 150 Ω (unbalanced)
Dynamic range	> 112,5 dB
Crosstalk	> 95dB
Audio Over IP	
Protocols	Dante® / AES67
Number of digital input ports	8
Number of digital output ports	8
Interfaces	1 x RJ-45 - NET2
Connectivity	
Ethernet	2, RJ-45 connector NET1 & NET2 (no switch capability)

Serial port Programming and control	Ethernet Base-Tx 10 /100Mb, 1Gb Auto X-Over	
	RS-232, Euroblock, 3-pin connector	
	EclerPLEX (Web application), TPNET (UDP/RS232), UCP control panels	
X-LINK		2, X-LINK ports. USB-C connector
Remote Control Connections		
	GPIs	8, 0 to 12VDC
	GPOs	8, 3 poles isolated relay; Contact rating: 2A, 30VDC; 0,5A, 125 VAC
Real-Time Clock		
	Retention time	> 5
	Accuracy	±1 minute / month
Local Storage		
	Micro SD	SDXC
	Capacity	Up to 2TB
	File system	FAT16, FAT 32, VFAT (read/write) NTFS (read)
Playable audio files	Multi-partition up to 1	
	mp3, ogg, WAV, FLAC, AIFF	
	Files analysis	
Folder hierarchy	65354 playable folders	
	65354 playable folders within each folder	
	65354 playable files within each folder	
Sorting	Up to 8 containing the root directory	
	UNICODE, in alphabetical order	
	Up to 100 folders / files by folder	
		Folders/files over 100 sorted in the FAT order
Electrical		
	Power supply	Internal.
	AC mains requirement	Universal, regulated switching mode supply
	AC mains connector	90-264 VAC @ 47-63Hz
Power consumption	IEC C14 inlet	
	16 W	
	32 VA	
Heat load	55 BTU / hour	
	Ventilation	
		FAN
Physical		
Operating temperature	Min: 0°C ; 32°F	
	Max: 50°C ; 122°F	
Operating humidity	5 - 85% RH, non-condensing	
Storage temperature	Min: 0°C ; 32°F	
	Max: 50°C ; 122°F	
Storage humidity	5 - 85% RH, non-condensing	
Installation options	Desktop, 19" racks (1RU)	
Included accessories	Power cord, Euroblock connectors, 2 USB-C holders	
Dimensions (WxHxD)	482.4 x 44 x 214 mm / 18.99 x 1.73 x 8.43 in.	
Weight	3.2 kg / 7.05 lb	
Shipping dimensions (WxHxD)	585 x 385 x 75 mm / 23.03 x 15.15 x 2.95 in.	
Shipping weight	4.65 kg/ 10.25 lb	

MECHANICAL DIAGRAM



Ecler VIVO-X8D8 Mechanical Diagram



6I-114I-0200

www.ecler.com



All product characteristics are subject to variation due to production tolerances. NEEC AUDIO BARCELONA S.L. reserves the right to make changes or improvements in the design or manufacturing that may affect these product specifications.

For technical queries contact your supplier, distributor or complete the contact form on our website, in [Support / Technical requests](#).

Motors, 166-168 - 08038 Barcelona - Spain | Tel. (+34) 932238403 | information@ecler.com | www.ecler.com