



PA LINE

PA

cmatic[®]
P N E U M A T I C F I T T I N G S

NPT黄铜镀镍标准接头
Brass Nickel-Plated Standard Fittings, NPT



PA系列通常被认为是“附件”或“标准接头”系列，由螺纹转接头，减径接头，堵头，软管接头、L型接头、T型接头、十字接头组成。考虑到这些接头所覆盖的各种辅助功能，很明显本系列能够为其它系列带来补充。
PA系列所有接头均经过镀镍表面处理。



The PA line, also known as the “Accessories line” or the “Standard Fitting line” consists of a wide variety of components, such as Nipples, Reduction pieces, Connections, Plugs, Hose connections, L-T and Cross Fitting.
Due to the multiple auxiliary functions of this line, the PA Fitting are the right complement for other ranges.
All components are brass nickel-plated.

接头本体
Fitting Body

镀镍黄铜 UNI EN 12164 CW614N - UNI EN 12165 CW617N
Brass UNI EN 12164 CW614N - UNI EN 12165 CW617N Nickel Plated



-40°C - 150°C



最大60 bar



	10-32 UNF	G1/8	G1/4	G3/8	G1/2	1/8 NPTF	1/4 NPTF	3/8 NPTF	1/2 NPTF
	•	•	•	•	•	•	•	•	•


应用领域：
气动、液压和油压系统。

Application fields:
Pneumatic, hydraulic and oleodynamic circuits.

PA 14

锥螺纹减径接头

Taper Female-Male Reducing Connector




类型	D1 NPTF	D2 NPTF	L1	L2	HEX	g Δ
14 1/8 10-32	1/8	10-32 UNF	8.5	15	12	-
14 1/4 1/8	1/4	1/8	13	19	14	12.30
14 3/8 1/8	3/8	1/8	13	19	18	-
14 3/8 1/4	3/8	1/4	13	19	18	18.00
14 1/2 1/4	1/2	1/4	17	24	22	-
14 1/2 3/8	1/2	3/8	17	24	22	-

PA 16

内外螺纹转接头

Adaptor Male-Female, taper




类型	D1 UNF	D2 BSP	L1	L2	HEX	g Δ
16 10-32 M5	10-32	M5x0.8	5	12	8	12.00

类型	D1 NPTF	D2 BSP	L1	L2	HEX	g Δ
16 1/8 1/8	1/8	G1/8	8.5	19	18	12.00
16 1/4 1/4	1/4	G1/4	13	27	18	26.50
16 3/8 3/8	3/8	G3/8	13	27	22	38.50
16 1/2 1/2	1/2	G1/2	17	34	27	66.50

PA 17

内外螺纹转接头

Adaptor Male-Female, parallel




类型	D1 BSP	D2 NPTF	L1	L2	HEX	g Δ
17 1/8 1/8	G1/8	1/8	6	18	14	12.50
17 1/4 1/4	G1/4	1/4	8	24	18	27.00
17 3/8 3/8	G3/8	3/8	9	25	22	49.50
17 1/2 1/2	G1/2	1/2	10	30	24	50.00

PA 19

堵头

Male Plug



类型	D1 NPTF	L1	L2	HEX	g Δ
19 00 1/8	1/8	8.5	12.5	12	6.50
19 00 1/4	1/4	13	18	14	14.50
19 00 3/8	3/8	13	18	18	24.50
19 00 1/2	1/2	17	23	22	-