



OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI 169 - Special Purpose Food Equipment and Devices

This is the Official Listing recorded on February 16, 2026.

C.MATIC S.p.A.
Via Matteotti, 28-32
20833 Giussano (MB)
Italy
39 036 280 5246

Facility: Giussano, Italy

COMPONENTS:

Fittings - Nickel Plated Brass Series ^[Pb]

AV12 (1)(2)(3) ^[1]	AV13 (1)(2) ^[1]	AV16 (1)(2) ^[1]	AV19 (1)(2) ^[1]
AV21 (1)(2) ^[1]	AV25 (1)(1) ^[1]	AV26 (1)(1) ^[1]	AV27 (1)(1) ^[1]
AV27 (1)(2) -F ^[1]	AV28 (1)(1) ^[1]	AV29 (1)(1) ^[1]	AV35 (1)(2) ^[1]
AV37 (1)(1) ^[1]	AV38 (1)(2) ^[1]	AV39 00 (1) ^[1]	AV40 00 (1) ^[1]
RV46 00 (2) ^[1]			

Fittings - Stainless Steel Series ^{[2] [Pb]}

CX10 (1)(2)	CX11 (1)(2)(5)
CX13 (1)(2)	CX14 (1)(2)
CX15 (1)(2)(5)	CX20 (1)(2)
CX23 (1)(2)	CX26 (1)(3)
CX28 (1)(3)	CX29 (1)(1)
GX10-11 00 (2)	GX10-12 00 (2)
GX10-13 (6) 00	GX10-20 00 (2)
GX10-21 00 (2)	GX10-22 (6) 00
GX30-10 00 (2) (5)	GX30-12 00 (2)
GX30-13 (6) 00	GX30-20 00 (2) (5)
GX30-21 00 (2)	GX30-22 (6) 00
GX31-10 00 (2) (5)	GX31-12 00 (2)
GX31-13 (6) 00	GX31-20 00 (2) (5)
GX31-21 00 (2)	GX31-22 (6) 00
GX31-30 00 (2) (5)	GX31-31 00 (2)
GX31-32 (6) 00	GX46-10 00 (2)
GX46-12 00 (2)	GX46-13 00 (2)
MX11 (1)(2)(5)	MX12 (1)(2)
MX13 (1)(2)	MX14 (1)(2)
MX15 (1)(2)(5)	MX16 (1)(2)
MX20 (1)(2)	MX21 (1)(2)
MX25 (1)(3)	MX26 (1)(3)
MX27 (1)(3)	MX28(1)(3)
MX29 (1)(1)	MX31 00 (2)

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



MX35 (1)(2) OX10 00 (1)
 OX11 (1) (2)(5) OX13 (1) (2)
 OX14 (1) (2) OX20 (1) (2)
 OX22 00 (1) OX26 (1) (3)
 OX28 (1) (3) OX29 (1) (1)
 PCX11 (1) (2) (5) PCX15 (1) (2) (5)
 POX11 (1) (2) (5) PUX10-11 00 (2)
 PUX10-12 00 (2) PUX10-20 00 (2)
 PUX10-21 00 (2) PVX11 00 (2)
 PVX18 (1) (2) / (4) PVX23 00 (2)
 PVX24 (7) (2) (5) PVX25 (7) (2) (5)
 PVX33 (1) (2) (5) PX11 (1)(2)(5)
 PX15 (1)(2)(5) PX20 (1)(2)
 PX25 (1)(1) PX26 (1)(3)
 PX27 (1)(3) PX28 (1)(3)
 PX29 (1)(1) RX12 (2)(2)
 RX13 00 (2) RX14 (2)(2)
 RX15 (2)(2) RX16 (2)(2)
 RX21 (2)(2) RX22 (2)(2)
 RX23 (2)(2) RX24 (2)(2)
 RX25 (2)(2) RX35(2)(2)
 RX42 00 (2) RX43 00 (2)
 RX44 00 (2) RX46 00 (2)
 VX11 00 (2) VX15 00 (2)/(4)
 VX18 (1)(2)/(4) VX21 00 (2)/(4)
 VX23 00 (2) VX24 (2)(5)(7)
 VX25 (2)(5)(7) VX33 (1) (2)(5)
 VX45 (2) (2) RX /U + K
 Fittings MF and RF Series^{[3] [10] [Pb]}
 MF12 (1)(2) MF13 (1)(2) MF16 (1)(2) MF21 (1)(2)
 MF24 (1)(2) MF26 (1)(1) MF28 (1)(1) MF29(1)(1)
 MF93 (1)(1) MF94 (2) (2) /B RF12 (2) (2) RF13 00 (2)
 RF14 (2) (2) RF16 (2) (2) RF19 00 (2) RF20 00 (2)
 RF21 (2) (2) RF22 (2) (2) RF23 (2) (2) RF24 (2) (2)
 RF25 (2) (2) RF30 (4) (2) RF35 (2) (2) RF36 (2) (2)
 RF45 (2) (2) RF47 00 (2) VF21 (2) (2) /B VF23 (2) (2) (5)
 VF24 00 (2) VF25 00 (2) VF33 (1) (6) (3)
 Fittings MY Series
 MY12 (1) (2)^{[7] [Pb]} MY12 (1) (2) -F^{[3] [7] [Pb]}
 MY12 (1) (2) -K^{[7] [8]} MY12 (1) (2) -X^{[7] [Pb]}
 MY13 (1) (2)^{[7] [Pb]} MY13 (1) (2) -F^{[3] [7] [Pb]}
 MY13 (1) (2) -K^{[7] [8]} MY13 (1) (2) -X^{[7] [Pb]}
 MY16 (1) (2)^{[7] [Pb]} MY16 (1) (2) -F^{[3] [7] [Pb]}
 MY16 (1) (2) -K^{[7] [8]} MY16 (1) (2) -X^{[7] [Pb]}
 MY21 (1) (2)^{[7] [Pb]} MY21 (1) (2) -F^{[3] [7] [Pb]}
 MY21 (1) (2) -K^{[7] [8]} MY21 (1) (2) -X^{[7] [Pb]}
 MY24 (1) (2)^{[7] [Pb]} MY24 (1) (2) -F^{[3] [7] [Pb]}

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



MY24 (1) (2) -K [7] [8] MY24 (1) (2) -X [7] [Pb]
MY25 (1) (1) [9] [Pb] MY26 (1) (1) [9] [Pb]
MY28 (1) (1) [9] [Pb] MY29 (1) (1) [9] [Pb]
MY37 (1) (1) [9] [Pb] MY39 00 (1) (1) [9] [Pb]
MY40 00 (1) [9] [Pb] MY43 (1) (1) [9] [Pb]
MY44 (1) (1) [9] [Pb] MY90 (1) (1) [9] [Pb]

- [1] (1) 2 digits indicating Diameter External Tube
(2) 2 digits indicating Thread Size
(3) 3 possible digits indicating different External Form - Empty is standard form
- [2] (1) up to 4 digits, character or numbers, indicating external tube diameter
(2) up to 4 digits, character or numbers, indicating thread size (standard form) or external tube or specific form
(3) up to 4 digits, character or numbers, indicating the external second tube diameter
(4) 1 digit, character, indicating the direction of the flow control
(5) up to 5 digits, character or numbers, indicating different external form or size - empty for standard form
(6) 2 digit indicating size for hose connection diameter
(7) up to 4 digits, character or numbers, indicating external tube diameter - 00 for same thread size
- [3] Models are acceptable for use in contact with coffee, tea and water.
- [4] (1) 2 digits indicating Diameter External
(2) 2 digits indicating Thread Size
- [5] (1) 2 digits indicating Diameter External Tube
- [6] (1) 2 digits indicating Thread Size
- [7] (1) 2 digits indicating Diameter External Tube
(2) 2 digits indicating Thread Size
- [8] Certified for use as part of a food equipment item with a resulting overall weighted average lead content of = 0.25% in the water contact portion of the equipment.
- [9] (1) 2 digits indicating Diameter External Tube
- [10] (1) 2 digits indicating Diameter External Tube
(2) 2 digits indicating Thread Size
(3) up to 2 digits indicating different External Form - Empty is standard form.
(4) up to 4 digits indicating hose connector diameter
(5) 2 digits indicating thread configuration
(6) 2 digits indicating diameter thread size (standard) or external tube
- [Pb] Product also evaluated and determined to possess weighted average lead content of <=0.25% and complies with lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.