
BuzziCane

Product Specification Sheet

This document contains technical
information about the BuzziCane



www.buzzi.space



A soft lounge sofa on an unexpected frame

With its woven cane back, wood base, and luscious upholstery, the BuzziCane sofa brings a fresh, vintage inspired look into the contemporary workplace. This sofa mixes a firm, elevated structure with plush seat and back cushions that are perfect for relaxing. Created by Dutch designers Wiebe Boonstra and Marc van Nederpelt, BuzziCane recalls the playful aesthetic that made them famous. The informal design welcomes guests with its friendly feel. BuzziCane is ideal for hotel suites, private offices and homes. It is available as a one, two or three seater.

Design by Wiebe Boonstra & Marc van Nederpelt

General

 DO 101 | DO 102 | DO 103

Frame in Ash Natural or Ash Black Stained

Webbing in Natural Cane

Filling cushions: 50% latex-sticks

 50% Comforell (polyester fiber balls)

All cushions finishing with 4 mm cord piping

Cushions upholstered in Fabric, Trevira CS+ | CS, Revive 1, Clara 2, Velvet, Hero 2, Tonus 4, Memory 2

 Dry use

Certifications

Filling cushions Seat & Back: CAL TB-117 (2013, Sec. 3)

Content

Configurations	3
Fabrics	4
Finishes	7
Dimensions	8

Configurations

DO 101

Frame in Ash Natural or Ash Black Stained

Webbing in Natural Cane

Filling cushions: 50% latex-sticks

50% Comforell (polyester fiber balls)



All cushions finishing with 4 mm cord piping


Cushions upholstered in Fabric, Trevira CS+ | CS,

Revive 1, Clara 2, Remix 3, Velvet, Hero 2,

Tonus 4, Memory 2



W 89 cm	H 65 cm	D 91 cm
W 35.04"	H 25.59"	D 35.83"



DO 102

Frame in Ash Natural or Ash Black Stained

Webbing in Natural Cane

Filling cushions: 50% latex-sticks

50% Comforell (polyester fiber balls)



All cushions finishing with 4 mm cord piping


Cushions upholstered in Fabric, Trevira CS+ | CS,

Revive 1, Clara 2, Remix 3, Velvet, Hero 2, Tonus 4,

Memory 2



W 199 cm	H 65 cm	D 91 cm
W 78.35"	H 25.59"	D 35.83"



DO 103

Frame in Ash Natural or Ash Black Stained

Webbing in Natural Cane

Filling cushions: 50% latex-sticks

50% Comforell (polyester fiber balls)



All cushions finishing with 4 mm cord piping

Cushions upholstered in Fabric,


Trevira CS+ | CS, Revive 1, Clara 2,

Remix 3, Velvet, Hero 2, Tonus 4,

Memory 2




W 268 cm	H 65 cm	D 91 cm
W 105.51"	H 25.59"	D 35.83"



Fabrics

Fabric (45 colors)



Category A

Composition 70% Recycled Wool, 25% Recycled Polyacryl,
5% Recycled Other Fabrics

Weight 405 g/m² | 11.94 oz/yd²

Abrasion resistance 40.000 Martindale, 50,000 Wyzenbeek

Flammability EU: EN 1021.1/2006 | BS EN 1021.1/2006 (cigarette).
EN 1021.2/2006 | BS EN 1021.2/2006 (match)
USA: CAL TB 117 | ASTM E84 CLASS A


Fastness to light EU: 4 | USA 4

Fastness to rubbing EU: Wet 3-4 | Dry 4-5

Fastness to crocking USA: Wet 5 | Dry 5



Trevira CS+ | CS (47 colors)



Category A

Weight 420 g/m² | 12.39 oz/yd²

Composition 100% Polyester, Trevira CS

Abrasion resistance 100.000 Martindale, 90,000 Wyzenbeek

Flammability BS 5852 part II: CRIB 5 | BS 7176 Medium Hazard
USA: CAL TB 117 | M1 | B1 | EN 1021/1-2 | C1 |
IMO Res. A652 (16)


Fastness to light EU: 6 | USA 5

Fastness to rubbing EU: Wet 4-5 | Dry 4-5

Fastness to crocking USA: Wet 5 | Dry 5



Revive 1 (25 colors)



Category A

Composition 100% recycled polyester FR

Weight 430 g/lin.m

Abrasion resistance 60.000 Martindale rubs, EN ISO 12947

Flammability EN 1021-1/2 | DIN 4102 B1 | Önorm B1/Q1
UNI 9175 1IM | US Cal. Tech. Bull. 117
IMO A.652 (16)

Fastness to light Note 5-7, ISO 105-B02


Fastness to rubbing (ISO) dry 5, wet 4-5

Pilling Note 4-5, EN ISO 12945



kvadrat


Velvet (12 colors)



Category B
Composition 100% PES
Weight 375 g/m² | 11.06 oz/yd²
Abrasion resistance > 100.000 Martindale
Fastness to light EU: 4-5
Fastness to rubbing EU: Wet 4 | Dry 4-5
Pilling EU: 4-5

Clara 2 (24 colors)

kvadrat



Category B
Composition 92% new wool, 8% nylon
Weight 400 g/lin.m
Abrasion resistance 80.000 Martindale rubs, EN ISO 12947
Flammability EN 1021-1/2 | BS 5852, ignition source 2-3 | DIN 4102 B2
NF D 60 013 | UNI 9175 1IM | US Cal. Tech. Bull. 117, Sec. E
NFPA 260 | IMO A.652(16)
Fastness to light Note 5-7, ISO 105-B02
Fastness to rubbing (ISO) dry 4-5, wet 4
Pilling Note 4, EN ISO 12945



Remix 3 (73 colors)

kvadrat




Category B
Composition 90% new wool, 10% nylon
Weight 415 g/lin.m
Abrasion resistance 100.000 Martindale rubs, EN ISO 12947
Flammability EN 1021-1/2 | BS 5852 part 1
Önorm B1/Q1 | NF D 60 013 | UNI 9175, 1IM
AS/NZS 1530.3 | Cal. Tech. Bull. 117-2013
NFPA 260 | IMO FTP Code 2010:Part 8
Fastness to light Note 5-7, ISO 105-B02
Fastness to rubbing (ISO) dry 4-5, wet 4
Pilling Note 4, EN ISO 12945



Hero 2 (33 colors)

kvadrat



Category C
Composition 97% new wool, 3% nylon
Weight 580 g/lin.m
Abrasion resistance 45.000 Martindale rubs, EN ISO 12947
Flammability EN 1021-1/2 | DIN 4102 B2 | NF D 60 013
UNI 9175 1IM | US Cal. Bull. 117-2013 | NFPA 260
IMO A.652 (16)
Fastness to light Note 5-6, ISO 105-B02
Fastness to rubbing (ISO) dry 4-5, wet 4-5
Pilling Note 3-4, EN ISO 12945



Tonus 4 (47 colors)

kvadrat



Category D

Composition 90% new wool, 10% Helanca

Weight 665 g/lin.m

Abrasion resistance 100.000 Martindale rubs, EN ISO 12947

Flammability EN 1021-1/2 | BS 5852 part 1 | DIN 4102 B2

Önorm B1/Q1 | NF D 60 013 | UNI 9175 11M

US Cal. Bull. 117-2013 | NFPA 260 | IMO A.652 (16)

Fastness to light Note 5-7, ISO 105-B02


Fastness to rubbing (ISO) dry 3-5, wet 3-5

Pilling Note 3, EN ISO 12945



Memory 2 (20 colors)

kvadrat



Category E

Composition 100% Trevira CS

Weight 700 g/lin.m

Abrasion resistance

35.000 rubs acc. to the Martindale method, EN ISO 12947

Flammability EN 1021-1/2 | DIN 4102 B1 | Önorm B1/Q1

NF D 60 013 | NF P 92 507 M1 | UNI 9175 11M

UNI 9177 classe 1 | US Cal. Tech. Bull. 117

IMO A.652 (16)

Fastness to light Note 5-8, ISO 105-B02

Fastness to rubbing (ISO) dry 4-5, wet 4-5

Pilling Note 4, EN ISO 12945



Finishes

Frame






Ash Natural




Ash Black Stained

Dimensions


DO 101




DO 101 Cushions




CUSHION 1






CUSHION 2




CUSHION 3 (Optional)




DO 102




DO 102 Cushions




CUSHION 1






CUSHION 2




CUSHION 3 (Optional)




DO 103




DO 103 Cushions



CUSHION 1



CUSHION 2



CUSHION 3 (Optional)

