Product Specification Sheet

BuzziPleat Light us

— By 13&9 Design

An avant-garde solution
BuzziPleat Light delivers exceptional sound control with an architectural edge thanks to its architectural folds made from our hero material, BuzziFelt. The suspended lighting solution can be equipped with BuzziSol, a powerful LED light source, or a retrofit option.

The Family

Models

Lighting Units	BuzziPleat Light Edel	BuzziPleat Light Edel Long	BuzziPleat Light Ripple
Retrofit E26 (bulb excluded)			
LED Solo Globe			
LED Solo Spot			
LED Trio Globe			
LED Trio Spot			
LED Quintet Globe			
LED Quintet Spot			

Required order information

1. Model
2. Size
3. BuzziFelt Color
4. Option Extra Layer BuzziFabric
5. Light Option
6. Mounting System
7. Color Lace

Lighting Data

Lighting Units

Retrofit Lighting unit

BuzziSol Solo retrofit includes 1 x E26 fitting.
BuzziSol Trio retrofit includes 3 x E26 fitting.
Bulb excluded, max.100W

LED

Globe



BuzziSol is a LED fixture consisting of 1 (BuzziProp Small) or 3 (BuzziProp Beam) powder-coated black heatsink with LED chip on board (COB) light source(s).
The product can be finished with a frosted glass globe diffuser which spreads the light in a large beam angle of 170°, enlighting the surroundings or a reflector spot adaptor directing the light with a beam angle of 38° downwards.

Spot



BuzziPleat Light

Model: Edel | Ripple
Medium |Large

Lighting Options		Characteristics		Mounting
Lighting Unit	**Voltage Input**	**Technical**	**Visual**	**Options**
Retrofit Solo	110-120V	Wattage: Max. 100W	Color: Power Cable: Black Ceiling Canopy: Black	1 cable of 78.74″- 196.85″ Alu or Black

Lighting Options					Characteristics		Mounting
Lighting Unit	**Voltage Input**	**Color Temperature**	**UGR (Diffuser type)**	**Dimming**	**Technical**	**Visual**	**Options**
LED Solo	110-120V	3000K	23 (Globe)	1-10V DALI	Power consumption: 20W Light output: 1500 Lm Efficacy: 75 Lm/W CRI: > 90	Color: Power Cable: Black Ceiling Canopy: Black	1 cable of 78.74″- 196.85″ Alu or Black
			12 (Spot)	1-10V DALI	Power consumption: 20W Light output: 1500 Lm Efficacy: 75 Lm/W CRI: >w 90		

Model: Light Edel Long Medium

Lighting Options		Characteristics		Mounting
Lighting Unit	**Voltage Input**	**Technical**	**Visual**	**Options**
Retrofit Trio	110-120V	Wattage: 3 x Max. 100W	Color: Power Cable: Black Ceiling Canopy: Black	4 cables of 78.74″- 196.85″ Alu or Black

Lighting Options					Characteristics		Mounting
Lighting Unit	**Voltage Input**	**Color Temperature**	**UGR (Diffuser type)**	**Dimming**	**Technical**	**Visual**	**Options**
LED Trio	110-120V	3000K	23 (Globe)	1-10V	Power consumption: 60W Light output: 3 x1500 Lm Efficacy: 92 Lm/W CRI: > 90	Color: Power Cable: Black Ceiling Canopy: Black	4 cables of 78.74″- 196.85″ Alu or Black
			12 (Spot)	1-10V	Power consumption: 60W Light output: 3 x1500 Lm Efficacy: 92 Lm/W CRI: > 90		

Model: Light Edel Long Medium

Lighting Options					Characteristics		Mounting
Lighting Unit	**Voltage Input**	**Color Temperature**	**UGR (Diffuser type)**	**Dimming**	**Technical**	**Visual**	**Options**
LED Quintet	110-120V	3000K	23 (Globe)	1-10V	Power consumption: 90W Light output: 5 x 1500 Lm Efficacy: 92 Lm/W CRI: > 90	Color: Power Cable: Black Ceiling Canopy: Black	4 cables of 78.74"- 196.85" Alu or Black
			12 (Spot)	1-10V	Power consumption: 90W Light output: 5 x 1500 Lm Efficacy: 92 Lm/W CRI: > 90		

Photometric Data

BuzziPleat Light BuzziSol Solo

LED Solo Globe Cartesian diagram



LED Solo Globe Polar curve



LED Solo Spot Cartesian diagram



LED Solo Spot Polar curve



BuzziPleat Light BuzziSol Trio

LED Trio Globe Cartesian diagram



LED Trio Globe Polar curve



LED Trio Spot Cartesian diagram



LED Trio Spot Polar curve



BuzziPleat Light BuzziSol Quintet

LED Quintet Globe Cartesian diagram



LED Quintet Globe Polar curve



LED Quintet Spot Cartesian diagram



LED Quintet Spot Polar curve



Tips and Tricks - Light Options

To enlight your workplace with optimal lux levels take following measurements into account:

BuzziPleat Light BuzziSol Solo

Solo Spot

Office,
Meeting room



500 Lux

Solo Globe

Office,
Meeting room



100 Lux

BuzziPleat Light BuzziSol Trio

Trio Spot

Office,
Meeting room



500 Lux

Trio Globe

Office,
Meeting room



500 Lux

BuzziPleat Light BuzziSol Quintet

Quintet Spot

Office
Meeting room



500 Lux

Quintet Globe

Office,
Meeting room



500 Lux

* According to EN12464

Product Data

Fixing System

Fixing System Acoustic Panel







BuzziPleat Light Edel and Ripple are suspended on 3 cables of 78.74" or 196.85" black or alu colored cables, with fixing system screw.

BuzziPleat Light Edel Long is suspended on 4 cables of 78.74" or 196.85" black or alu colored cables, with fixing system screw.



Fixing System Lighting
The light element of BuzziPLeat Light Edel Long is suspended independently from the acoustic panel with 2 cables of 78.74" or 196.85" black or alu colored cables, with fixing system screw.

⚠ If installing on suspended ceiling, verify load capacity prior to installation.
Ensure a min distance of 3.94" between the felt shade and the LED luminaire.

Acoustic Panel

The acoustic panel consists of one layer of BuzziFelt, with an OffWhite or Black lace.
The lightweight sculptural shade is created by pleating or smocking sound absorbing BuzziFelt.
The architectural folds maximize surface area, delivering exceptional acoustic performance.

Absorption

Diffusion

Mid tone

High tone

Optional: an extra layer of BuzziFabric can be added on 1 side (only in combination with OffWhite or Anthracite Felt).

Acoustics Data

BuzziPleat Ceiling Suspended

Equivalent sound absorption area in m² per object



Hz	Edel M Aeq/m²	Edel L Aeq/m²	Edel Long M Aeq/m²	Ripple M Aeq/m²	Ripple L Aeq/m²
125	0.18	0.54	0.58	0.14	0.20
250	0.32	0.92	0.87	0.39	0.50
500	0.63	1.64	1.49	0.92	0.90
1000	0.94	2.13	2.48	1.19	1.30
2000	1.11	2.56	2.80	1.39	1.40
4000	1.30	2.75	2.92	1.59	1.70

Dimensions

BuzziPleat Light Ripple LED





Height

M	5.12″
L	7.68″





Width

M	Ø 39.37″
L	Ø 59.06″

BuzziPleat Light Ripple Retrofit



Height

M	5.12″
L	7.68″



Width

M	Ø 39.37″
L	Ø 59.06″

BuzziPleat Light Edel LED



Height

M 3.54″
L 5.31″





Width

M Ø 39.37″
L Ø 59.06″

BuzziPleat Light Edel Retrofit



Height	**M**	3.54″
	L	5.31



Width	**M**	Ø 39.37″
	L	Ø 59.06″

BuzziPleat Light Edel Long Trio LED





BuzziPleat Light Edel Long Trio Retrofit





BuzziPleat Light Edel Long Quintet LED





Weights

BuzziPleat Light Ripple Medium | Large BuzziSol Solo Retrofit



Medium: 13.89 lbs
Large: 26.46 lbs

BuzziPleat Light Ripple Medium | Large BuzziSol Solo LED



Medium: 14.77 lbs
Large: 27.34 lbs

BuzzuPleat Light Edel Medium | Large BuzziSol Solo Retrofit



Medium: 11.68 lbs
Large: 22.05 lbs

BuzzuPleat Light Edel Medium | Large BuzziSol Solo LED



Medium: 12.57 lbs
Large: 22.93 lbs

BuzziPleat Light Edel Long Trio BuzziSol Trio Retrofit



25.57 lbs

BuzziPleat Light Edel Long Trio BuzziSol Trio LED



30.86 lbs

BuzziPleat Light Edel Long Quintet BuzziSol Quintet LED



36.38 lbs

Fabrics

Felt

Composition 100% Recycled P.E.T. Felt, latex backing
Weight 1.000 g/m2 | 29.49 oz/yd2
Abrasion resistance >7.000 Martindale
Flammability EU: EN 13501.1 + A1/2009 Class B-s1,d0
USA: ASTM E84 Class A certified
Fastness to light USA 5

FE-OffWhite 63*



FE-StoneGrey 67



FE-Anthracite 68*

*Extra layer BuzziFabric Possible

Fabric (45 colors)



Category A
Composition 70% Recycled Wool, 25% Recycled Polyacryl,
5% Recycled Other Fabrics
Weight 405 g/m² | 11.94 oz/yd²
Abrasion resistance 40.000 Martindale, 50,000 Wyzenbeek
Flammability EU: EN 1021.1/2006 | BS EN 1021.1/2006 (cigarette).
EN 1021.2/2006 | BS EN 1021.2/2006 (match)
USA: CAL TB 117 | ASTM E84 CLASS A
Fastness to light EU: 4 | USA 4
Fastness to rubbing EU: Wet 3-4 | Dry 4-5
Fastness to crocking USA: Wet 5 | Dry 5

Acoustics

BuzziPleat Ceiling

Equivalent sound absorption area in m² per object



Hz	Edel M Aeq/m²	Edel L Aeq/m²	Edel Long M Aeq/m²	Ripple M Aeq/m²	Ripple L Aeq/m²
125	0.18	0.54	0.58	0.20	0.50
250	0.32	0.92	0.87	0.50	1.50
500	0.63	1.64	1.49	0.90	2.40
1000	0.94	2.13	2.48	1.20	2.80
2000	1.11	2.56	2.80	1.40	3.20
4000	1.30	2.75	2.92	1.60	3.50