CERTIFICATEOF COMPLIANCE



BuzziSpace NV

BuzziFold

296952-410

Certificate Number

22 Dec 2022 - 14 May 2025

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Wall finishes are determined compliant using an Office Environment with an air change of o.68 hr⁻¹ and a loading of 33.40 m².

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.





GREENGUARD Certification Criteria for Furniture and Mattresses

Criteria	CAS Number	Maximum Allowable Predicted Concentration	Units
TVOC _(A)	-	0.50	mg/m³
Formaldehyde	50-00-0	61.3 (50 ppb)	μg/m³
Total Aldehydes (B)	-	0.10	ppm
4-Phenylcyclohexene	4994-16-5	6.5	μg/m³
Individual VOCs (C)	-	1/10th TLV	-

- (A) Defined to be the total response of measured VOCs falling within the C6 C16 range, with responses calibrated to a toluene surrogate.
- (B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.
- (C) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).



