



Product Specification Sheet

BuzziShade US

— By Stal Collectief

The BuzziShade combines lit surroundings with acoustic performance.

The design prevents eavesdroppers from hearing your private conversations, and reduces external noise levels to a minimum. The BuzziShade is extremely versatile. The perfect addition to any office, waiting room or restaurant and is ideal for large-scale events. Be creative in colour by adding a layer of fabric to the BuzziFelt shades. The BuzziShade is the culmination of an artistic collaboration between BuzziSpace and the four young Belgian furniture designers of Stal Collectief.



The Family

Models

BuzziShade M

BuzziShade L


BuzziShade XL

BuzziShade XXL


Retrofit E26
(bulb excluded)





**Sol Solo
Globe**





Sol Solo Spot



**No
Electrification**



**LED Disk
Ø 470**



Lighting Units

Required order information

1. Size
2. Light Option
3. Color Frame
4. BuzziFelt Color

5. Option Extra Layer Inside or Outside
6. Color Lace
7. Mounting Option
8. Color Ceiling Canopy (only for Retrofit)
9. Color Power Cable (only for Retrofit)

Lighting Data

Lighting Units


Retrofit Lighting unit (only available for BuzziShade M | L)



Retrofit E26 bulb excluded, Max 100W.


BuzziSol (only available for BuzziShade M | L)

Globe



BuzziSol Solo is a suspended LED fixture consisting of 1 powder-coated black heatsink with LED chip on board (COB) light source. The product can be finished with a frosted glass globe diffuser which spreads the light in a large beam angle of 170°, enlighting the surroundings or a reflector spot adaptor directing the light with a beam angle of 38° downwards.

Spot




No Electrification (only available for BuzziShade XL | XXL)



On request, the BuzziShade XL or XXL can be ordered without LED light Source

LED Disk Ø 470 (only available for BuzziShade XL | XXL)



The PMMA diffuser ensures an optimal light spread and efficiency. It creates a very diffuse light surface without any dottiness.

The light source is a LED PCB, containing 36 low power LED's.

BuzziShade

Model: Medium | Large

Lighting Options

Lighting Unit Voltage Input

Characteristics

Technical

Visual

Mounting

Options

Retrofit
E26
bulb excl.

110-120V

Wattage: Max. 100W

Color:
Power Cable: Black

Ceiling Canopy:
Black

Metal Frame:
Black, White,
Fluorescent Orange

Lace:
Black, White,
Fluorescent Orange

2 cables of
78.74" or 196.85"
Alu or Black

Lighting Options

Lighting Unit Voltage Input

Color Temperature

UGR (Diffuser type)

Dimming

Characteristics

Technical

Visual

Mounting

Options

LED
Solo

100-240V/277V

2700K
3000K
3500K
4000K

23 (Globe)

1-10V

Power consumption: 19W
Light output: 1500 Lm
Efficacy: 79 Lm/W
CRI: > 90

Color:
Power Cable:
Black

Ceiling Canopy:
Black

Metal Frame:
Black, White,
Fluorescent Orange

Lace:
Black, White,
Fluorescent Orange

2 cables of
78.74" or
196.85"
Alu or Black

12 (Spot)

1-10V

Power consumption: 19W
Light output: 1500 Lm
Efficacy: 79 Lm/W
CRI: > 90

Model: XL | XXL

Lighting Unit Voltage Input

Color Temperature

UGR (Diffuser type)

Dimming

Technical

Visual

Options

LED Disk
Ø 470

120-277V

3000K
3500K

22 (milky)

1-10V

Power consumption: 29W
Light output: 2545 Lm
Efficacy: 88 Lm/W
CRI: > 90

Color:
Power Cable:
Black

Ceiling Canopy:
Black

Metal Frame:
Black, White

Lace:
Black, White

3 cables of
78.74" or
196.85"
Alu or Black




* To achieve a UGR 19, the product is fitted with a Prismatic diffuser instead of a milky diffuser. LED dots will be visible.


Photometric Data

BuzziShade BuzziSol Solo


Sol Solo Globe Cartesian diagram




Sol Solo Globe Polar curve



Sol Solo Spot Cartesian diagram




Sol Solo Spot Polar curve




BuzziShade LED Disk Ø 470

LED Disk Ø 470 Cartesian diagram



LED Disk Ø 470 Polar curve




Tips and Tricks - Light Options

To enlight your workplace with optimal lux levels take following measurements into account:

BuzziShade BuzziSol Solo


Solo Spot

Office,
Meeting room




Solo Globe

Office,
Meeting room




BuzziShade LED Disk Ø 470


Office,
Meeting room




Reception desk, Lounge,
classroom



Entrance Hal



Entrance Hall






* According to EN12464

Product Data

Fixing System

Fixing System Acoustic Shade



BuzziShade M and L are suspended on 2 cables of 78.74" or 196.85" black or alu colored cables, with fixing system screw.

BuzziShade XL and XXL are suspended on 3 cables of 78.74" or 196.85" black or alu colored cables, with fixing system screw.

⚠ If installing on suspended ceiling, verify load capacity prior to installation.

Acoustic Shade



The acoustic shade consists of one layer of BuzziFelt with our signature lacing.

BuzziShade M | L : Lace in Black, White or Fluorescent Orange.

BuzziShade XL | XXL : Lace in Black or White.

Two rows of lacing for size XL and three rows for size XXL

Optional: an extra layer of BuzziFabric can be added on the inside or outside.



Absorption



Mid tone




High tone

Metal Frame




BuzziShade M I L : Powder coated metal frame in Black (RAL 9005), White (RAL 9010), Fluo Orange (RAL 2005)



BuzziShade XL I XXL : Powder coated metal frame in Black (RAL 9005), White (RAL 9010)
The metal frame is built up in 2 parts for XL and 3 parts for XXL

Acoustics


BuzziShade Equivalent sound absorption area in m² per object




Hz	Shade M Aeq/m²	Shade L Aeq/m²	Shade XL Aeq/m²	Shade XXL Aeq/m²
125	0.27	0.60	1.00	1.51
250	0.32	0.70	1.52	2.09
500	0.36	0.80	2.03	2.55
1000	0.50	1.10	2.59	3.16
2000	0.63	1.40	3.15	4.06
4000	0.68	1.50	3.60	4.87

Dimensions


BuzziShade Pendant Medium




BuzziShade Pendant LED Medium




BuzziShade Pendant Large




BuzziShade Pendant LED Large






BuzziShade XXL




Weights

BuzziShade M Retrofit




8.82 lbs

BuzziShade L Retrofit




17.64 lbs

BuzziShade M BuzziSol




13.23 lbs

BuzziShade L BuzziSol




22.05 lbs

BuzziShade XL



46.74 lbs


BuzziShade XXL



56.66 lbs

Fabrics

Felt (12 colors)



Composition 100% Recycled P.E.T. Felt, latex backing

Weight 1.000 g/m² | 29.49 oz/yd²


Abrasion resistance >7.000 Martindale

Flammability EU: EN 13501.1 + A1/2009 Class B-s1,d0
USA: ASTM E84 Class A certified

Fastness to light USA 5



Fabric (45 colors)



Category A

Composition 70% Recycled Wool, 25% Recycled Polyacryl,
5% Recycled Other Fabrics

Weight 405 g/m² | 11.94 oz/yd²

Abrasion resistance 40.000 Martindale, 50,000 Wyzenbeek

Flammability EU: EN 1021.1/2006 | BS EN 1021.1/2006 (cigarette).
EN 1021.2/2006 | BS EN 1021.2/2006 (match)
USA: CAL TB 117 | ASTM E84 CLASS A

Fastness to light EU 4 | USA 4

Fastness to rubbing EU: Wet 3-4 | Dry 4-5

Fastness to crocking USA: Wet 5 | Dry 5

