
BuzziChicle Planter

Product Specification Sheet

This document contains technical
information about the BuzziChicle Planter



www.buzzi.space



An acoustic room divider with integrated planters

BuzziChicle Planter is a soft, sound-absorbing room divider with integrated plant pots, available in Round or Rectangular models. Made from 80% post-consumer recycled jeans and CARB II/PEFC-certified wood, it supports both acoustic comfort and sustainable design. Pair with real or artificial plants to create biophilic, calming environments in open-plan offices, lounges, or hospitality spaces.

Design by Common Object Studio

General



Round | Rectangular

Core: MDF



Filling: Acoustic material made of 80% recycled cotton fibres

Cover: Fabric, Trevira CS, Revive 1, Clara 2, Remix 3, Hero 2, Tonus 4, Arda, Memory 2



Dry use

Acoustics



Absorption



Diffusion



Mid tone




High tone

Content

Configurations	3
Components	4
Fabrics	5
Dimensions	8

Configurations

Round




Core: MDF
Filling: Acoustic material made of 80% recycled cotton fibres
Cover: Fabric, Trevira CS, Reflect, Clara 2, Remix 3, Hero 2, Tonus 4, Arda, Memory 2

✕ Height 60 cm Width 60 cm
Height 23.62" Width 23.62"

⚖ 16 kg | 35.27 lbs

Rectangular



Core: MDF
Filling: Acoustic material made of 80% recycled cotton fibres
Fabric, Trevira CS, Reflect, Clara 2, Remix 3, Hero 2, Tonus 4, Arda, Memory 2

✕ Height 60 cm Width 113 cm Depth 43 cm
Height 23.62" Width 44.49" Depth 16.93"

⚖ 29 kg | 63.93 lbs

Components

Bottom



Bottom: Black MDF with plastic feet

Round: 5x plastic feet
Rectangular: 6x plastic feet

Container




Black Plastic Container

Round: 1x 12L Container
Rectangular: 3x 12L Containers

12L Container:
Width Ø 31,5 cm Height 23 cm
Width Ø 12.40" Height 9.06"

Fabrics

Fabric (45 colors)



Category A

Composition 70% Recycled Wool, 25% Recycled Polyacryl,
5% Recycled Other Fabrics

Weight 405 g/m² | 11.94 oz/yd²

Abrasion resistance 40.000 Martindale, 50,000 Wyzenbeek

Flammability EU: EN 1021.1/2006 | BS EN 1021.1/2006 (cigarette).
EN 1021.2/2006 | BS EN 1021.2/2006 (match)
USA: CAL TB 117 | ASTM E84 CLASS A


Fastness to light EU: 4 | USA 4

Fastness to rubbing EU: Wet 3-4 | Dry 4-5

Fastness to crocking USA: Wet 5 | Dry 5



Trevira CS (47 colors)



Category A

Weight 420 g/m² | 12.39 oz/yd²

Composition 100% Polyester, Trevira CS

Abrasion resistance 100.000 Martindale, 90,000 Wyzenbeek

Flammability BS 5852 part II: CRIB 5 | BS 7176 Medium Hazard
USA: CAL TB 117 | M1 | B1 | EN 1021/1-2 | C1 |
IMO Res. A652 (16)


Fastness to light EU: 6 | USA 5

Fastness to rubbing EU: Wet 4-5 | Dry 4-5

Fastness to crocking USA: Wet 5 | Dry 5



Revive 1 (25 colors)



Category A

Composition 100% recycled polyester FR

Weight 430 g/lin.m

Abrasion resistance 60.000 Martindale rubs, EN ISO 12947

Flammability EN 1021-1/2 | DIN 4102 B1 | Önorm B1/Q1
UNI 9175 1IM | US Cal. Tech. Bull. 117
IMO A.652 (16)

Fastness to light Note 5-7, ISO 105-B02


Fastness to rubbing (ISO) dry 5, wet 4-5

Pilling Note 4-5, EN ISO 12945



kvadrat

Reflect (34 colors)


**Category A****Weight** 430 g/m² | 13.78 oz/yd²**Composition** 100% Post-consumer recycled polyester**Abrasion resistance** 100.000 Martindale**Flammability** AS/NZS 3837 class 1 | ASTM E84 Class A Unadhered

ASTM E84 Class B Adhered | BS 5852 crib 5 with treatment

BS 5852 part 1 with treatment | EN 1021-1/2 | US Cal. Bull. 117-2013

Fastness to light Note 5-7, ISO 105-B02**Fastness to rubbing** EU: Wet 5-5 | Dry 5-5**Pilling** Note 4, EN ISO 12945

Clara 2 (24 colors)

kvadrat**Category B****Composition** 92% new wool, 8% nylon**Weight** 400 g/lin.m**Abrasion resistance** 80.000 Martindale rubs, EN ISO 12947**Flammability** EN 1021-1/2 | BS 5852, ignition source 2-3 | DIN 4102 B2

NF D 60 013 | UNI 9175 1IM | US Cal. Tech. Bull. 117, Sec. E

NFPA 260 | IMO A.652(16)

Fastness to light Note 5-7, ISO 105-B02**Fastness to rubbing** (ISO) dry 4-5, wet 4**Pilling** Note 4, EN ISO 12945

Remix 3 (73 colors)

kvadrat**Category B****Composition** 90% new wool, 10% nylon**Weight** 415 g/lin.m**Abrasion resistance** 100.000 Martindale rubs, EN ISO 12947**Flammability** EN 1021-1/2 | BS 5852 part 1


Önorm B1/Q1 | NF D 60 013 | UNI 9175, 1IM

AS/NZS 1530.3 | Cal. Tech. Bull. 117-2013

NFPA 260 | IMO FTP Code 2010:Part 8

Fastness to light Note 5-7, ISO 105-B02**Fastness to rubbing** (ISO) dry 4-5, wet 4**Pilling** Note 4, EN ISO 12945

Hero 2 (33 colors)

kvadrat**Category C****Composition** 97% new wool, 3% nylon**Weight** 580 g/lin.m**Abrasion resistance** 45.000 Martindale rubs, EN ISO 12947**Flammability** EN 1021-1/2 | DIN 4102 B2 | NF D 60 013

UNI 9175 1IM | US Cal. Bull. 117-2013 | NFPA 260

IMO A.652 (16)

Fastness to light Note 5-6, ISO 105-B02**Fastness to rubbing** (ISO) dry 4-5, wet 4-5**Pilling** Note 3-4, EN ISO 12945

Tonus 4 (47 colors)

kvadrat



Category D

Composition 90% new wool, 10% Helanca

Weight 665 g/lin.m

Abrasion resistance 100.000 Martindale rubs, EN ISO 12947

Flammability EN 1021-1/2 | BS 5852 part 1 | DIN 4102 B2

Önorm B1/Q1 | NF D 60 013 | UNI 9175 11M

US Cal. Bull. 117-2013 | NFPA 260 | IMO A.652 (16)

Fastness to light Note 5-7, ISO 105-B02


Fastness to rubbing (ISO) dry 3-5, wet 3-5

Pilling Note 3, EN ISO 12945



Arda (12 colors)

kvadrat



Category E

Composition 70% new wool 21% polyester 9% nylon

Weight 800 g/lin. m | 25.8 oz/ly

Abrasion resistance

Approx. 50.000 Martindale rubs, EN ISO 12947

Flammability ASTM E84 Class A Unadhered | AS/NZS 3837 class 2 | BS 5852 part 1

BS 5852 crib 5 | DIN 4102 B2 | EN 1021-1/2 | IMO FTP Code 2010 Part 8

UNI 9175 11M | US Cal. Bull. 117-2013

Fastness to light Note 5-8, ISO 105-B02

Fastness to rubbing Dry note 3-5 ISO 105-X12


Wet note 3-5 ISO 105-X12

Pilling Note 4, EN ISO 12945



Memory 2 (20 colors)

kvadrat



Category E

Composition 100% Trevira CS

Weight 700 g/lin.m

Abrasion resistance

35.000 rubs acc. to the Martindale method, EN ISO 12947

Flammability EN 1021-1/2 | DIN 4102 B1 | Önorm B1/Q1

NF D 60 013 | NF P 92 507 M1 | UNI 9175 11M

UNI 9177 classe 1 | US Cal. Tech. Bull. 117

IMO A.652 (16)

Fastness to light Note 5-8, ISO 105-B02



Fastness to rubbing (ISO) dry 4-5, wet 4-5

Pilling Note 4, EN ISO 12945



Dimensions

Round



Dimensions

Rectangular

