




Product Specification Sheet

BuzziTrom US

— By BuzziSpace Studio

Functional lighting with acoustic power

BuzziTrom is the first functional acoustic lighting solution crafted from a dual layer of felt that works on speech and high-tones. Along with an integrated LED disk, this acoustic lighting pendant houses an enclosed 4 cm air cavity that ensures maximum acoustic performance. Its cylindrical design traps sound waves within the radius of its frame; meanwhile, the exterior helps to diffuse sound energy.



The Family

Sizes




BuzziTrom S

BuzziTrom M

BuzziTrom L

Lighting Unit

**LED Disk
Ø 470**




Required order information

1. Size
2. BuzziFelt Color
3. Mounting Option
4. Option

Lighting Data

Lighting Unit

LED Disk Ø 470



The PMMA diffuser ensures an optimal light spread and efficiency. It creates a very diffuse light surface without any dottiness. The light source of the BuzziTrom is a LED PCB, containing 36 low power LED's.

BuzziDome Lighting options


Lighting Options				Characteristics		Mounting
Voltage Input	Color Temperature	UGR (Diffuser type)	Dimming	Technical	Visual	Options
120-277V	3000K 3500K	22 (milky)	1-10V	Power consumption: 29W Light output: 2545 Lm Efficacy: 88 Lm/W CRI: > 90	Color: Power Cable: Black Ceiling Canopy: Black	1 cable 78.74" 196.85" Alu or Black




Photometric Data

BuzziTrom S | M | L LED Disk Ø 470

LED Disk Ø 470 Cartesian diagram







LED Disk Ø 470 Polar curve



Tips and Tricks - Light Options

To enlight your workplace with optimal lux levels take following measurements into account:

BuzziTrom S | M | L LED Disk Ø 470






* According to EN12464

Product Data



Fixing System

Ceiling Suspended Split



Ceiling Suspended Split
Fixing System Screw with 3 split cables and 1 main cable, total length of 78.74" or 196.85" (black or alu)
Min. distance of shade to ceiling is 19.70"

Ceiling Suspended Straight



Ceiling Suspended Straight
Fixing System Screw with 3 cables of 78.74" or 196.85" (black or alu)
Min. distance of shade to ceiling is 3.90"

⚠ If installing on suspended ceiling, verify load capacity prior to installation.

Acoustic Shade



The acoustic shade consists of two layers of BuzziFelt, finished with push buttons in glossy black.

The Light source is wrapped with a felt ring in the same felt color as the inside of the shade.

Bicolor is optional: inside/outside in a different BuzziFelt color.



Diffusion



Attenuation



Mid tone




High tone

Acoustics

BuzziTrom

Equivalent sound absorption area in m² per object




Hz	S Aeq/m²	M Aeq/m²	L Aeq/m²
125	0.34	0.60	0.88
250	0.34	0.60	0.88
500	0.52	0.90	1.31
1000	0.68	1.18	1.73
2000	0.89	1.54	2.23
4000	0.85	1.47	2.14



Dimensions

BuzziTrom S

Straight




Split





BuzziTrom M

Straight




Split





BuzziTrom L

Straight




Split




Weights

BuzziTrom S




22.93 lbs

BuzziTrom M



27.78 lbs


BuzziTrom L



30.42 lbs

Fabrics

Felt (15 colors)



Composition 100% Recycled P.E.T. Felt, latex backing

Weight 1.000 g/m2 | 29.49 oz/yd2

Abrasion resistance >7.000 Martindale

Flammability EU: EN 13501.1 + A1/2009 Class B-s1,d0
USA: ASTM E84 Class A certified

Fastness to light USA 5

