
BuzziBlinds

Product Specification Sheet

This document contains technical information about the BuzziBlinds



www.buzzi.space



Acoustical performance and privacy with a twist

After the introduction in 2011 BuzziBlinds Classic became an instant hit as partitions for open-plan spaces. Five years later it's time to add some zest to the family. BuzziBlinds are inspired on modernist architecture. The rhythm and tonalities created by the orientation of the V-cut BuzziBlinds add a dynamic of depth to any space. The free-standing room divider is made up of a series of five rotating acoustic blinds. With a simple twist, the blinds can be opened or closed to varying degrees to create privacy or open-up a space. This gives individuals the opportunity to determine the level of privacy they may want or need at any given moment to concentrate on a specific task. BuzziBlinds consists of 4 different shapes. The Blinds are covered with plane BuzziFelt. Adding a V-cut feature to the BuzziFelt enhances a stronger architectural look in your space.

Design by Alain Gilles

General

📍 Straight | Wedge | Beach | Arch
M | L

🌲 Baseplate: powder coated metal
Blinds: core aluminium
BuzziFelt cover

☁️ Dry use

🔧 Flat packed

Baseplate colour in black (RAL 9005) or white (RAL 9010)

Blinds felt with or without V-cut

Optional felt printed (not possible for V-cut)

- Optional extra layer Fabric, Trevira CS, Reflect, Revive 1, Clara 2, Remix 3, Hero 2, Tonus 4, Arda, Memory 2 (extra layer not possible for V-cut)
- Multicolour (front & back different colour)
- Wheels (4pcs)

Acoustics



Attenuation



Diffusion



Absorption



Mid tones



High tones

Certifications





Content

Configurations	3	Dimensions	12
Overview	5	Acoustics	14
Fabrics	7		

Configurations

BuzziBlinds Straight



M | L

Baseplate: powder coated metal



Blinds: aluminium core
BuzziFelt cover

M: H 150 cm W 149 cm D 49 cm
H 59.06" W 58.66" D 19.29"



L: H 185 cm W 149 cm D 49 cm
H 72.83" W 58.66" D 19.29"



M: 45 kg | 99.21 lbs
L: 49 kg | 108.03 Lbs

Baseplate color in black (RAL 9005) or white (RAL 9010)

Blinds felt with or without V-cut

Optional Felt printed (not possible for V-cut)





Optional extra layer Fabric, Trevira CS, Reflect, Revive 1, Clara 2, Remix 3, Hero 2, Tonus 4, Arda, Memory 2 (extra layer not possible for V-cut)

Multicolor (front & back different color)

Wheels (4pcs)

BuzziBlinds Wedge



M | L

Baseplate: powder coated metal



Blinds: aluminium core
BuzziFelt cover

M: H 155 cm W 149 cm D 49 cm
H 61.02" W 58.66" D 19.29"



L: H 190 cm W 149 cm D 49 cm
H 74.80" W 58.66" D 19.29"



M: 45 kg | 99.21 lbs
L: 49 kg | 108.03 Lbs

Baseplate color in black (RAL 9005) or white (RAL 9010)

Blinds felt with or without V-cut

Optional Felt printed (not possible for V-cut)





Optional extra layer Fabric, Trevira CS, Reflect, Revive 1, Clara 2, Remix 3, Hero 2, Tonus 4, Arda, Memory 2 (extra layer not possible for V-cut)


Multicolor (front & back different color)

Wheels (4pcs)

BuzziBlinds Beach



Beach
Front - Back



Beach V-cut
lines 1 Front



Beach V-cut
lines 1 Back

🔑 M | L

Baseplate: powder coated metal

🌲 Blinds: aluminium core
BuzziFelt cover

M: H 155 cm W 149 cm D 49 cm
H 61.02" W 58.66" D 19.29"

✂

L: H 190 cm W 149 cm D 49 cm
H 74.80" W 58.66" D 19.29"

⚖

M: 45 kg | 99.21 lbs
L: 49 kg | 108.03 lbs


Baseplate color in black (RAL 9005) or white (RAL 9010)

Blinds felt with or without V-cut


Optional Felt printed (not possible for V-cut)

⋮ Optional extra layer Fabric, Trevira CS, Reflect, Revive 1, Clara 2, Remix 3, Hero 2, Tonus 4, Arda, Memory 2 (extra layer not possible for V-cut)
Multicolor (front & back different color)
Wheels (4pcs)

BuzziBlinds Arch



Arch
Front - Back



Arch V-cut lines 1
Front - Back

🔑 M | L

Baseplate: powder coated metal

🌲 Blinds: aluminium core
BuzziFelt cover

M: H 149 cm W 149 cm D 49 cm
H 58.66" W 58.66" D 19.29"

✂

L: H 184 cm W 149 cm D 49 cm
H 72.44" W 58.66" D 19.29"

⚖

M: 45 kg | 99.21 lbs
L: 49 kg | 108.03 Lbs

Baseplate color in black (RAL 9005) or white (RAL 9010)

Blinds felt with or without V-cut

Optional Felt printed (not possible for V-cut)

⋮ Optional extra layer Fabric, Trevira CS, Revive 1, Clara 2, Remix 3, Hero 2, Tonus 4, Memory 2 (extra layer not possible for V-cut)
Multicolor (front & back different color)
Wheels (4pcs)

Overview

BuzziBlinds Straight M|L




Straight
Front




Straight
Back

M: H 145 cm W 33 cm L: H 180 cm W 33 cm
 H 57.09" W 12.99" H 70.87" W 12.99"

BuzziBlinds Straight V-cut M|L




Straight V-cut lines 1
Front



Straight V-cut lines 1
Back

M: H 145 cm W 33 cm L: H 180 cm W 33 cm
 H 57.09" W 12.99" H 70.87" W 12.99"

BuzziBlinds Wedge M|L



Wedge
Front




Wedge
Back

M: H 150 cm W 33 cm L: H 185 cm W 33 cm
 H 59.06" W 12.99" H 72.83" W 12.99"

BuzziBlinds Wedge V-cut M|L




Wedge V-cut lines 1
Front



Wedge V-cut lines 1
Back

M: H 150 cm W 33 cm L: H 185 cm W 33 cm
 H 59.06" W 12.99" H 72.83" W 12.99"

BuzziBlinds Beach M|L




Beach
Front

Beach
Back

M: H 150 cm W 33 cm L: H 185 cm W 33 cm
H 59.06" W 12.99" H 72.83" W 12.99"

BuzziBlinds Beach V-cut M|L




Beach V-cut lines 1
Front

Beach V-cut lines 1
Back

M: H 150 cm W 33 cm L: H 185 cm W 33 cm
H 59.06" W 12.99" H 72.83" W 12.99"

BuzziBlinds Arch M|L




Arch
Front

Arch
Back

M: H 144 cm W 33 cm L: H 179 cm W 33 cm
H 56.59" W 12.99" H 70.47" W 12.99"

BuzziBlinds Arch V-cut M|L




Arch V-cut lines 1
Front

Arch V-cut lines 1
Back

M: H 144 cm W 33 cm L: H 179 cm W 33 cm
H 56.59" W 12.99" H 70.47" W 12.99"

Fabrics


Felt (15 colors)



Composition 100% Recycled PE.T. Felt, latex backing
Weight 1.000 g/m² | 29.49 oz/yd²
Abrasion resistance >7.000 Martindale
Flammability EU: EN 13501.1 + A1/2009 Class B-s1,d0
USA: ASTM E84 Class A certified
Bottle, Mustard, Mint, Nude: USA: ASTM E85 Class C Certified
Fastness to light USA 5




Fabric (45 colors)



Category A
Composition 70% Recycled Wool, 25% Recycled Polyacryl,
5% Recycled Other Fabrics
Weight 405 g/m² | 11.94 oz/yd²
Abrasion resistance 40.000 Martindale, 50,000 Wyzenbeek
Flammability EU: EN 1021.1/2006 | BS EN 1021.1/2006 (cigarette).
EN 1021.2/2006 | BS EN 1021.2/2006 (match)
USA: CAL TB 117 | ASTM E84 CLASS A
Fastness to light EU: 4 | USA 4
Fastness to rubbing EU: Wet 3-4 | Dry 4-5
Fastness to crocking USA: Wet 5 | Dry 5



Trevira CS (47 colors)




Category A
Weight 420 g/m² | 12.39 oz/yd²
Composition 100% Polyester, Trevira CS
Abrasion resistance 100.000 Martindale, 90,000 Wyzenbeek
Flammability BS 5852 part II: CRIB 5 | BS 7176 Medium Hazard
USA: CAL TB 117 | M1 | B1 | EN 1021/1-2 | C1 |
IMO Res. A652 (16)
Fastness to light EU: 6 | USA 5
Fastness to rubbing EU: Wet 4-5 | Dry 4-5
Fastness to crocking USA: Wet 5 | Dry 5



Reflect (34 colors)

kvadrat



Category A

Weight 430 g/m² | 13.78 oz/yd²

Composition 100% Post-consumer recycled polyester

Abrasion resistance 100.000 Martindale

Flammability AS/NZS 3837 class 1 | ASTM E84 Class A Unadhered

ASTM E84 Class B Adhered | BS 5852 crib 5 with treatment

BS 5852 part 1 with treatment | EN 1021-1/2 | US Cal. Bull. 117-2013

Fastness to light Note 5-7, ISO 105-B02


Fastness to rubbing EU: Wet 5-5 | Dry 5-5

Pilling Note 4, EN ISO 12945



Revive 1 (25 colors)

kvadrat



Category A

Composition 100% recycled polyester FR

Weight 430 g/lin.m

Abrasion resistance 60.000 Martindale rubs, EN ISO 12947

Flammability EN 1021-1/2 | DIN 4102 B1 | Önorm B1/Q1

UNI 9175 1IM | US Cal. Tech. Bull. 117

IMO A.652 (16)


Fastness to light Note 5-7, ISO 105-B02

Fastness to rubbing (ISO) dry 5, wet 4-5

Pilling Note 4-5, EN ISO 12945



Velvet (12 colors)



Category B

Composition 100% PES

Weight 375 g/m² | 11.06 oz/yd²

Abrasion resistance > 100.000 Martindale


Fastness to light EU: 4-5

Fastness to rubbing EU: Wet 4 | Dry 4-5

Pilling EU: 4-5

Clara 2 (24 colors)

kvadrat



Category B

Composition 92% new wool, 8% nylon

Weight 400 g/lin.m

Abrasion resistance 80.000 Martindale rubs, EN ISO 12947

Flammability EN 1021-1/2 | BS 5852, ignition source 2-3 | DIN 4102 B2

NF D 60 013 | UNI 9175 1IM | US Cal. Tech. Bull. 117, Sec. E

NFPA 260 | IMO A.652(16)

Fastness to light Note 5-7, ISO 105-B02

Fastness to rubbing (ISO) dry 4-5, wet 4

Pilling Note 4, EN ISO 12945



Remix 3 (73 colors)

kvadrat



Category B

Composition 90% new wool, 10% nylon

Weight 415 g/lin.m

Abrasion resistance 100.000 Martindale rubs, EN ISO 12947

Flammability EN 1021-1/2 | BS 5852 part 1

Önorm B1/Q1 | NF D 60 013 | UNI 9175, 1IM

AS/NZS 1530.3 | Cal. Tech. Bull. 117-2013

NFPA 260 | IMO FTP Code 2010:Part 8

Fastness to light Note 5-7, ISO 105-B02


Fastness to rubbing (ISO) dry 4-5, wet 4

Pilling Note 4, EN ISO 12945



Hero 2 (33 colors)

kvadrat



Category C

Composition 97% new wool, 3% nylon

Weight 580 g/lin.m

Abrasion resistance 45.000 Martindale rubs, EN ISO 12947

Flammability EN 1021-1/2 | DIN 4102 B2 | NF D 60 013

UNI 9175 1IM | US Cal. Bull. 117-2013 | NFPA 260

IMO A.652 (16)

Fastness to light Note 5-6, ISO 105-B02

Fastness to rubbing (ISO) dry 4-5, wet 4-5

Pilling Note 3-4, EN ISO 12945



Tonus 4 (47 colors)

kvadrat



Category D

Composition 90% new wool, 10% Helanca

Weight 665 g/lin.m

Abrasion resistance 100.000 Martindale rubs, EN ISO 12947

Flammability EN 1021-1/2 | BS 5852 part 1 | DIN 4102 B2

Önorm B1/Q1 | NF D 60 013 | UNI 9175 1IM

US Cal. Bull. 117-2013 | NFPA 260 | IMO A.652 (16)

Fastness to light Note 5-7, ISO 105-B02

Fastness to rubbing (ISO) dry 3-5, wet 3-5

Pilling Note 3, EN ISO 12945



Arda (12 colors)

kvadrat



Category E

Composition 70% new wool 21% polyester 9% nylon

Weight 800 g/lin. m | 25.8 oz/ly

Abrasion resistance

Approx. 50.000 Martindale rubs, EN ISO 12947

Flammability ASTM E84 Class A Unadhered | AS/NZS 3837 class 2 | BS 5852 part 1
BS 5852 crib 5 | DIN 4102 B2 | EN 1021-1/2 | IMO FTP Code 2010 Part 8
UNI 9175 1IM | US Cal. Bull. 117-2013

Fastness to light Note 5-8, ISO 105-B02


Fastness to rubbing Dry note 3-5 ISO 105-X12
Wet note 3-5 ISO 105-X12

Pilling Note 4, EN ISO 12945



Memory 2 (20 colors)

kvadrat



Category E

Composition 100% Trevira CS

Weight 700 g/lin.m

Abrasion resistance

35.000 rubs acc. to the Martindale method, EN ISO 12947

Flammability EN 1021-1/2 | DIN 4102 B1 | Önorm B1/Q1
NF D 60 013 | NF P 92 507 M1 | UNI 9175 1IM
UNI 9177 classe 1 | US Cal. Tech. Bull. 117
IMO A.652 (16)

Fastness to light Note 5-8, ISO 105-B02

Fastness to rubbing (ISO) dry 4-5, wet 4-5

Pilling Note 4, EN ISO 12945



Felt Printed (not for possible for V-cut)

Composition 100% Recycled P.E.T. Felt, latex backing

Weight 1.000 g/m² | 29.49 oz/yd²

Abrasion resistance >7.000 Martindale


Flammability EU: EN 13501.1 + A1/2009 Class B-s1,d0

USA: ASTM E84 Class A certified

Fastness to light USA 5



Concrete



Green 1



Green 2



Jungle



Marble Absynth



Marble Emperador



Camo Amazon



Camo Taiga




Camo Desert






Camo Snow

Dimensions




BuzziBlinds Baseplate Regular



Acoustics

Equivalent sound absorption area in m² per object

BuzziBlind Wedge closed position



Hz	M Aeq/m ²	L Aeq/m ²
125	0.30	0.36
250	1.00	1.21
500	1.40	1.71
1000	2.10	2.57
2000	3.10	3.80
4000	3.70	4.54