

# Technical Data Sheet



## Vision Uniform Stretch Polyester

Material	100% Polyester
Stock widths	253cm / 320cm
Weight acc. to DIN EN 12127	215.00 (g/m <sup>2</sup> ) +/- 3%
Shrinkage	
Heat shrinkage, 195 degrees, 90sec length acc. to DIN EN 12127	-2.00% +/- 1%
Heat shrinkage, 195 degrees, 90sec width acc. to DIN EN 12127	-2.00% +/- 1%
Tearing strength	
Elongation at 100 N, longitudinal direction acc. to DIN EN ISO 13934-1	63% +/- 20%
Elongation at 100 N, cross direction acc. to DIN EN ISO 13934-1	7% +/- 20%
Maximum tensile elongation, longitudinal direction acc. to DIN EN ISO 13934-1	86% +/- 20%
Maximum tensile elongation, cross direction acc. to DIN EN ISO 13934-1	50% +/- 20%
Maximum tearing strength, longitudinal direction acc. to DIN EN ISO 13934-1	min. 510 N/5cm
Maximum tearing strength, longitudinal direction acc. to DIN EN ISO 13934-1	min. 750N/5cm
Flame retardency	B1 / EN13501



Roseash Limited, Unit B The Height Business Centre, Ibstone Road, Stokenchurch, Buckinghamshire, HP14 3BG  
T: 01494 760240 E : sales@dpm.com W : www.dpm.com