



## RGL1

### SINGLE LEG WEBBING LANYARD & SHOCK ABSORBER

An industry standard, and usually the minimum equipment issued/required with a harness for anyone working at height.

We use 32kN polyester webbing to manufacture this product which helps give the product a longer life. It is also treated with a water repellent coating which also extends the life of this product. This lanyard should be used when the operative is working from a static position, connected to a fixed anchor point.

If movement between anchorages is required, a twin leg lanyard should be used (RGL3) to provide constant protection.



Shock absorber

Accredited to: EN 355:2002

Web material: 26mm RIDGE Protect anti-bacterial polyester\*

Fittings: 17mm steel screwgate karabiner (RGK1) & any compatible EN 362 connectors

Max arrest force: <6kN

Length(s): 1.3m  
1.8m

\* 14 times reduction in bacterial growth, according to ISO 20743:2013 contact with *K.pneumoniae*, commonly associated with healthcare infections such as *E.coli*



RIDGEGEAR LIMITED

📍 Nelson Street, Leek, Staffordshire, ST13 6BB, UK

☎ +44 (0)1538 384 108

✉ sales@ridgegear.com

🌐 ridgegear.com

©2023 RIDGEGEAR Limited. All the information and imagery within this data sheet is subject to copyright. While we make every effort to ensure all the information here is correct and up-to-date, it is always worth checking with us before ordering. We reserve the right to change product specifications when necessary without prior notice.



Q05822