## **RIDGEGEAR PRODUCT DATA SHEET**



# RGHK4

## THE TWIN LEG SCAFFOLDER'S KIT

The twin leg version of our Scaffolder's Kit contains a two point safety harness and a twin leg fall arrest lanyard.

The addition of a twin leg lanyard means workers can safely and efficiently move between anchor points, whilst working close to an open edge. This version comes with two scaffold hooks meaning it is ideal for clipping to scaffolding or other steel structures.

Accredited to: EN 361:2002, EN 355:2002, EN 362:2004

Kit contains: Front & rear D harness (RGH2)

Twin leg webbing lanyard and shock absorber (RGL3)

17mm steel screwgate karabiner (RGK1)

60mm aluminium double-action scaffold hook with captive eye x 2

(RGK11)

#### See overleaf for specific item specifications





### **RIDGEGEAR PRODUCT DATA SHEET**

# **RGHK4**

### ITEM SPECIFICATIONS

Product: Front & rear D harness (RGH2)

Accredited to: EN 361:2002

Web material: 45mm RIDGE Protect anti-bacterial polyester\*

Fittings: High tensile steel alloy

Weight: 1.1kg

/ Front & rear attachment point

Product: Twin leg webbing lanyard and shock absorber (RGL3)

Accredited to: EN 355:2002

Web material: 26mm RIDGE Protect anti-bacterial polyester\*

Fittings: 17mm steel screwgate karabiner (RGK1)

60mm aluminium double-action scaffold hook with captive eye

(RGK11)

Max arrest force: <6kN

Length(s): 1.3m 1.8m

Product: 17mm steel screwgate karabiner (RGK1)

Accredited to: EN 362:2004

Material: Steel Plating: Zinc

Gate opening: 17mm External length: 107mm Closure type: Screwgate

MBS: 23kN Weight: 160g

Product: 60mm aluminium double-action scaffold hook with captive eye x 2

(RGK11)

Accredited to: EN 362:2004

Material: Aluminium
Plating: Anodised
Gate opening: 60mm
Eye diameter: 30mm
External length: 248mm
Closure type: Double action

MBS: 23kN Weight: 480g





<sup>\* 14</sup> times reduction in bacterial growth, according to ISO 20743:2013 contact with K.pneumoniae, commonly associated with healthcare infections such as E.coli