



RGL5

SINGLE LEG WEBBING RESTRAINT LANYARD

The restraint lanyard can only be used for work restraint because there is no shock absorption built into the system.

If there is any possibility of a fall, then a fall arrest product should be used. It should never be used to extend another fall arrest product.

We use 32kN polyester webbing to manufacture this product which helps give the product a longer life. It is also treated with a water repellent coating which also extends the life of this product.

Accredited to: EN 354:2010

Web material: 26mm RIDGE Protect anti-bacterial polyester*

Fittings: Supplied without connectors unless stated otherwise

Max arrest force: Restraint only - Not to be used as fall arrest

Length(s): 1m

1.3m

1.8m

(including connectors)

* 14 times reduction in bacterial growth, according to ISO 20743:2013 contact with *K.pneumoniae*, commonly associated with healthcare infections such as *E.coli*



RIDGEGEAR LIMITED

📍 Nelson Street, Leek, Staffordshire, ST13 6BB, UK

☎ +44 (0)1538 384 108

✉ sales@ridgegear.com

🌐 ridgegear.com

©2023 RIDGEGEAR Limited. All the information and imagery within this data sheet is subject to copyright. While we make every effort to ensure all the information here is correct and up-to-date, it is always worth checking with us before ordering. We reserve the right to change product specifications when necessary without prior notice.



Q05822